



## V7 UPS 750VA Desktop UK

### UPS1DT750-1K

SKU: J153412

This UPS provide a backup power source for desktop computers, network workstations and other professional and consumer electronic devices. It ensures a consistent flow of electricity to help prevent equipment failure and data loss during power failures, brownouts, or other power issues that can occur with power in your building. The USB port allows built in UPS configuration and control, and auto-shutdown features for your computers or servers.

- 750VA Desktop UPS with 6 Outlets (3 battery backup + 3 surge only)
- Convenient and compact desktop design with touch screen LCD to display UPS information
- Efficient and eco friendly power.
- USB connectivity to your PC for optional advanced monitoring and control
- Audio & Visual alarms for immediate warning of battery, load, and other issues

#### General

Sku: J153412  
 Model: UPS1DT750-1K  
 EAN: 0662919091403  
 Warranty: 3 Year (1 Year Battery)  
 Compliance: CE, REACH, RoHS  
 Country Of Origin: China  
 Package Type: 4 Color Box  
 SAP: 3369145  
 Package Includes: UPS System, USB Cable, Setup Guide, Warranty

#### Color

Color: Black

#### Design

UPS Style: Desktop

#### Other

Assurance: up to 100.000 € connected equipment assurance  
 Software: ViewPower for viewing, controlling, and monitoring your UPS systems and automatic computer shutdown. Shutdown Wizard for standalone software allowing automatic computer shutdown.

#### Package Dimensions

Package Dimensions (L/W/H): 14.8 x 5.59 x 9.33 in  
 (376 x 142 x 237 mm)  
 Shipping Weight: 4 kgs (8.82 lbs)

#### Product Dimensions

Product Dim (L/W/H): 12.01 x 6.24 x 3.74 in (305 x 158.5 x 95 mm)  
 Product Weight: 3.4 kg (7.5 lbs)

#### Technical

Voltage: 220/230/240 VAC  
 Battery Type: Sealed Lead Acid  
 Outlets: 6 (3 battery backup + 3 surge only)  
 Input AC Plug Type: BS 1363 (UK)  
 Communication/Configuration Ports: USB  
 Load Capacity (Watts): 450W  
 Load Capacity Volt Amp (VA): 750VA  
 Noise Level: Less than 40dB  
 Audible Alarms: Battery is on, Battery is Low, Overload or Wiring Fault  
 Category: Standby  
 Recharge Time: 8 hours recover to 90% capacity  
 Transfer Time: Typical 2-6 ms (max 10ms)  
 Waveform Type: Simulated Sine Wave  
 Backup Runtime: 5.5 minute half load  
 Frequency Range: 50/60 Hz (Auto sensing)  
 LED status light: AC Mode (Green), Battery (Flashing Yellow), Fault (Red)  
 Surge Protection: 632 Joules  
 Visual Indicator: Touch LCD: AC Mode, Battery mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault and Low Battery  
 Battery Volt Amp Hour Capacity: Local 12V/5AH (60)  
 Data Line Protection: RJ-11, RJ-45 (10/100)  
 AC Cord length: 1.83 m



## Specifications

<b>CAPACITY</b>	750 VA / 450 W
<b>INPUT</b>	
Voltage	220/230/240VAC
Acceptable Voltage Range	180 - 270VAC
Frequency Range	50 Hz / 60 Hz (Auto-sensing)
<b>OUTPUT</b>	
Voltage	220/230/240VAC
AC Voltage Regulation (Batt. Mode)	±10%
Frequency Range (Batt. Mode)	50 Hz / 60 Hz ±1 Hz
Transfer Time	Typical 2-6ms, 10ms Max.
Waveform (Batt. Mode)	Simulated Sinewave
<b>BATTERY</b>	
Battery Type & Number	12V / 5Ah x 1
Typical Recharge Time	8 hours recover to 90% capacity
<b>INDICATORS</b>	
AC Mode	Green LED
Battery Mode	Flashing Yellow LED
Fault	Flashing Red LED
<b>ALARM</b>	
Battery Mode	Sounds every 10 seconds
Low Battery	Sounds every second
Overload	Sounds every 0.5 second
Fault	Continuously sounds
<b>PROTECTION</b>	
Protection Types	Overload, discharge, and overcharge
<b>PHYSICAL</b>	
Dimensions: L x W x H:	305 x 158.5 x 95mm (12 x 6.24 x 3.74 in)
Net Weight:	3 kgs (6.71 lbs.)
<b>ENVIRONMENT</b>	
Humidity	0-90 % RH @ 0-40°C (non-condensing)
Noise Level	Less than 40dB