

## Power Double USB-C/A Socket

12-24 V DC, output 5 V DC, 3.6 Amp with integrated power voltage converter and blue LED. For charging and operating electronic devices that are suitable for charging by 5 V USB. Mounting hole Ø 28 mm. Fastening by hexagon nut. Panel thickness 2-16 mm.

## Technical Details:

- Connection: 1x USB-C and 1 x USB-A
- E1 certificate
- Input 8-34 V DC
- Output 3.6 Amp
- current consumption  $\leq 1$  m Amp.
- Overload protection
- over temperature protection
- reverse polarity protection
- short-circuit protection
- overvoltage protection during short voltage peaks
- Cable connection pre-assembled, approx. 15 cm, cable cross-section 0.5 mm<sup>2</sup>



## Our new USB-C/A Socket, 12-24 V DC, output 5 V DC, 3.6 Amp comes in different variations:

Bulk Packaging, loose in a box

| <b>Product Description</b>  | Item-No. | Sales-Unit | Price/pc net | Recommended<br>Retail Price | Product Picture |
|---|----------|------------|--------------|-----------------------------|-----------------|
| Power Double USB-C/A Socket  Mounting Hole Ø 28 mm fastening by hexagon nut Panel thickness 2-16 mm   | 67341000 | 100        | 10.90 €      | 24.90 €                     |                 |
| Power Double USB-C/A Socket with Mounting Plate  Mounting Hole Ø 36 mm – Panel thickness until 14 mm Mounting Hole Ø 36 mm – Panel thickness over 14 mm Fastening with hexagon nuts and enclosed screws   | 67342000 | 100        | 11.30 €      | 25.90 €                     |                 |
| Surface Mounted Power Double USB C/A Socket  Fastening with enclosed screws Dimensions (mm) L x H x W: 85 x 35 x 33   | 67343000 | 100        | 10.90 €      | 24.90 €                     |                 |
| Surface Mounted Triple Socket with 2 Power Sockets and 1 Power Double USB- C/A Socket Two power sockets (inner Ø 21 mm) for cooling boxes or devices that are suitable to be operated by 12-24 volt. One power double USB C/A socket  Load capacity max. 20 A with a supply cable cross-section of 2.5 mm2, max. 16 A with a supply cable cross-section of 1.5 mm2. Fixing by means of screws supplied. Pre-assembled cable connection. Dimensions L x W x H: 85 x 95 x 33 mm | 67344000 | 100        | 17.65 €      | 36.90 €                     |                 |

| <b>Product Description</b>  | Item-No. | Sales Unit | Price/pc net | Recommended<br>Retail Price | Product Picture |
|---|----------|------------|--------------|-----------------------------|-----------------|
| Triple Socket with 2 Power Sockets and 1 Power Double USB-C/A Socket  Two power sockets (inner Ø 21 mm) for cooling boxes or devices that are suitable to be operated by 12-24 volt.                                  | 67345000 | 50         | 22.20 €      | 45.90 €                     |                 |
| One power double USB C/A socket  Load capacity max. 16 A.Connection with universal plug fits in cigarette lighter (Ø 21 mm) and standard (Ø 12 mm) sockets. Cable length 2.0 m. Dimensions L x W x H: 85 x 95 x 38 mm |          |            |              |                             |                 |