

## 2-Port VGA Splitter Wall Plate (250MHz)

### General information

VS102 video splitters provides video input signals to 2 video outputs each at 250 MHz after duplication. Users can boost video signals from the video gain knob within a transfer range up to 65m.

#### Package Contents

- 1x 2-Port Video Splitter
- 1x 0AD6-1909-03EG Power Adapter
- 1x User Instructions

### Features

- One video input to 2 video outputs
- Cascadable to 3 levels-provides up to 8 video signals
- Supports up to 250 MHz bandwidth
- Long distance transmission - up to 65 m \*
- High video resolution - up to 1920 x 1440
- DDC, DDC2, DDC2B Compatible (Port 1 only)
- Supports VGA, XGA, SVGA, UXGA and multisync monitors
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun
- Compact design with convenient topside connection, lays flat on a desktop or mounts on the wall

\* Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality

### Specifications

Bandwidth:	250 MHz
Ports:	2-Port
Power consumption:	1.89 W
Dimensions:	103.6 x 79 x 28.2 mm
Input power:	9 W
Compatible power supply:	0AD6-1909-03EG
Function control:	Automatic



### Sales information

Order code:	<b>VS102-AT-G</b>
Product description:	2-Port VGA Splitter Wall Plate (250MHz)
Brand name:	Aten



Quantity	LxWxH (mm)	Weight
1	65x165x240	417 gr.

## 2-Port VGA Splitter Wall Plate (250MHz)

Supported technology:	VGA
Supported technology:	XGA
Supported technology:	SVGA
Supported technology:	UXGA
Max. resolution:	1920x1440
Electronic device type:	VGA
Outside material:	Metal
Packaging:	Box
Colour:	Black
Connection output:	2x VGA Female
Power plug:	Euro / Type C (CEE 7/16)
Connection input:	VGA Male