



PIN OUT

P1	1	2	3	4	6	5	7	9	8	10	12	11	15	16	17	18	19	SHELL
P2	2	1	3	10	9	11	18	17	19	23	24	22	6	7	15	14	16	SHELL
	BLUE	RED	WHITE	BLUE	WHITE	DRAIN	BLUE	WHITE	DRAIN	BLUE	WHITE	DRAIN	RED	WHITE	YELLOW	ORANGE	PURPLE	
		FAM		FAM			FAM			FAM								

P/N	L(mm)
11.99.5519	1000±30mm
11.99.5522	2000±50mm
11.99.5532	3000±70mm
11.99.5552	5000±70mm

1. MATERIAL
 1.1 HDMI CABLE: (7/0. 10TC*1P+7/0. 10TC+FAM)*4PCS+7/0. 12TC*3C+7/0. 12TC*1P +AL+7/0. 12TC+128/0. 12ALM+BLACK PVC JACKET.
 OD: $\varnothing 6.0 \pm 0.2$ mm

1.2 HDMI 19PIN TYPE A MALE : BLACK INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
 1.3 DVI (18+1) MALE: BLACK INSULATION, GOLD PLATED CONTACTS G/F, NICKEL PLATED SHELL.

1.4 THUMB SCREW TO BE MOLDED BLACK PVC. NICKEL PLATED SCREW.
 1.5 ALL HOOD: MOLDED BLACK PVC.

2. ELECTRICAL
 2.1 100% OPEN AND SHORT TEST.
 2.2 CONDUCTOR RESISTANCE: 5 OHMS MAX.
 2.3 INSULATION RESISTANCE: 10 MEGOHMS MIN.
 2.4 HI-POT: DC300V/0.01S.

3. PACKAGING: A PC/PE-BAG PACKAGING .
 4. ALL MATERIALS ARE REACH COMPLIANT.

LENGTH TOLERANCE: X. ± 0.5 .X ± 0.2 .XX ± 0.1	SCALE: FREE	UNIT: MM	VERSION: 02
ANGLE TOLERANCE: X' $\pm 3'$.X' $\pm 1'$	PAGE: 1/1		4

Rotronic Co., Ltd.		ENG:
VALUE DVI Cable, DVI M-HDMI M, black		CHECKED:
		APPROVED:

A 02	ADD THE ONE	2012-01-05
01	CHANGE THE CABLE MARKING	2011-02-23
00	NEW ISSUE	2010-03-16
REV.	MODIFY DESCRIPTION	DATE