


- ① 16 AMP OUTPUT CIRCUIT BREAKER SWITCH FOR IEC320-C19
- ② IEC320-C19 OUTPUT RECEPTACLE
- ③ 16 AMP OUTPUT CIRCUIT BREAKER SWITCH FOR IEC320-C19
- ④ IEC320-C19 OUTPUT RECEPTACLE

- ⑤ 10 AMP OUTPUT CIRCUIT BREAKER SWITCH FOR IEC320-C13
- ⑥ (4) IEC320-C13 OUTPUT RECEPTACLES
- ⑦ 10 AMP OUTPUT CIRCUIT BREAKER SWITCH FOR IEC320-C13
- ⑧ (4) IEC320-C13 OUTPUT RECEPTACLES

NOTES:

- 1. UNIT DIMENSIONS: 7.4" W x 5.7" H
(188mm) x (145mm)
- 2. UNIT WEIGHT: 4.4lbs (2.0kg)
- 3. SHIPPING DIMENSIONS: 11.9" H x 20.6" W x 8.7" D
(302mm) x (522mm) x (220mm)
- 4. SHIPPING WEIGHT: 6.6lbs (3.0kg)
- 5. ALL WIRING IS TO BE IN COMPLIANCE WITH NATIONAL AND LOCAL ELECTRICAL CODES.

DRAWN BY K. STACY	SHEET NO. 1 OF 1	POD PD2-201 WITH (2) IEC320-C19 AND (8) IEC320-C13 OUTPUT SOCKETS FOR GXT4-8000RT208 OR GXT4-10000RT208 UPS	DWG. NO. PD2-201	DATE 1/14/15	REV. # 1	1050 DEARBORN DRIVE P.O. BOX 29186 COLUMBUS, OHIO 43229	
	CHK BY G. FUNK						
REF. DWG.	ORDER NO.						