

# CYBEX™ SC800/SC900 SECURE DESKTOP DVI-I KVM SWITCHES



Superior security and control at the desktop  
NIAP PP 3.0 Compliant, Common Criteria Tested and Certified


## OVERVIEW

### KEY FEATURES

- Advanced isolation between computers and shared peripherals
- Support for DVI-I in single and dual head models supporting resolutions up to 2560 x 1600

### BENEFITS

- Compliant to NIAP Protection Profile for Peripheral Sharing Switches, version 3.0
- Unidirectional Optical Data Diodes assure USB peripheral isolation enabling data flow from devices to host only
- Always-on active anti-tampering system
- Dedicated Peripheral Port (DPP) for connecting authentication devices such as biometric readers and smart card readers
- Hardware-based peripheral isolation loads all firmware on ROM with no keyboard buffering or memory
- Full USB device filtering to assure support for keyboard and mouse only
- Mouse and keyboard switching via emulation assures zero delay in switching them between connected sources



### SPECIFICATIONS

MODEL NUMBER	SC820/SC920	SC840/SC845/SC940/SC945	SC885/SC985
System Connections	2	4	8
System Support	DVI-I, single-link/dual-link		
Display Connections	Single Head SC8xx, Dual Head SC9xx		
Display Support	DVI-I, single-link/dual-link		
Max Resolution	DVI dual-link - 2560 x 1600 @ 60Hz		
CONNECTIONS			
Console Peripherals	USB Type - A		
Computer Peripherals	USB Type - B		
Dedicated Peripheral Port	0	1 (SC845/SC945)	1
Audio Input/Output	1 x 3.5 mm stereo female		
MECHANICAL			
Enclosure	Steel with plastic front panel		
Dimensions W x D x H in/ (mm)	7 x 2.4 x 1.7 (178 x 61 x 43) SC8XX 7 x 2.4 x 2.2 (178 x 61 x 56) SC9XX	13.7 x 5 x 1.7 (348 x 127 x 43) SC8XX 13.7 x 5 x 2.2 (348 x 127 x 56) SC9XX	17.3 x 7.3 x 1.7 (439 x 185 x 43) SC8XX 17.3 x 7.3 x 2.2 (439 x 185 x 56) SC9XX
Weight lbs/ (kg)	1.0 (0.5) SC8XX / 1.5 (0.7) SC9XX	3.0 (1.5) SC8XX / 3.7 (1.9) SC9XX	5.4 (2.5) SC8XX / 6.8 (3.1) SC9XX
POWER			
Power Requirements	12V DC, 1.5A Power Adapter	35W Max Internal	45W Max Internal
AC Input Voltage	100 to 240V AC		
ENVIRONMENTAL			
Operating Temperature	32° to 104°F; 0° to 40°C		
Storage Temperature	-4° to 140°F; -20° to 60°C		
Humidity	0-80% RH, non-condensing		
Certifications	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada		
Warranty	3 Years		



SC845 front panel



SC845 rear panel

## Ordering Details

MODEL NUMBER	CABLE OPTIONS-LENGTH	CABLE DESCRIPTION
SC845/SC885	CBL0146 - 6 ft. , CBL0147 - 10 ft.	DVI-D, USB, AUDIO, DPP
SC945/SC985	CBL0148 - 6 ft. , CBL0149 - 10 ft.	DH DVI-D, USB, AUDIO, DPP
SC820/SC840	CBL0150 - 6 ft. , CBL0151 - 10 ft.	DVI-D, USB, AUDIO
SC920/SC940	CBL0152 - 6 ft. , CBL0153 - 10 ft.	DH DVI-D, USB, AUDIO

VertivCo.com | Vertiv Headquarters, 1050 Dearborn Drive, Columbus, OH, 43085, USA

© 2018 Vertiv Co. All rights reserved. Vertiv and the Vertiv logo are trademarks or registered trademarks of Vertiv Co. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness herein, Vertiv Co. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.