

VPU series

VPU III R 230V/6KV AC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Type III surge protection

- Compact Type III arrester for AC/DC protection acc. to IEC 61643-11:2012
- Suitable for protecting terminals
- Installed in the vicinity of the equipment to be protected
- Can be used as single-port arrester when nominal current is greater than 16 A

General ordering data

Type	VPU III R 230V/6KV AC
Order No.	1351650000
Version	Surge voltage arrester, Low voltage, with remote contact, Single-phase, $U_p(L/N-PE) \leq 1200 \text{ V}$
GTIN (EAN)	4050118158496
Qty.	1 pc(s).

VPU series

VPU III R 230V/6KV AC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	18 mm	Width (inches)	0.709 inch
Height	102 mm	Height (inches)	4.016 inch
Depth	71.5 mm	Depth (inches)	2.815 inch
Net weight	77 g		

Temperatures

Humidity	5 - 95% rel. humidity	Operating temperature, max.	70 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	70 °C
Storage temperature, min.	-40 °C	Operating temperature	-40 °C...70 °C
Storage temperature	-40 °C...70 °C		

Technical data, signal line

Rated current I_N	16 A
---------------------	------

Connection data, remote alert

Connection type	Screw connection	Max. torque	0.5 Nm
Stripping length	5 mm	Cross-section for connected wire, solid core, min.	0.2 mm ²
Cross-section for connected wire, solid core, max.	1.5 mm ²		

General data

Colour	orange	Design	Installation housing; 1TE, Insta IP 20
Optical function display	Green LED = OK, Red LED = arrester is defective, replace	Protection degree	IP20
Rail	TS 35	Segment	Power distribution
UL 94 flammability rating	V-0	Version	with remote contact

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	II
--------------------	---	------------------------	----

Rated data IEC / EN

Combined pulse U_{OC}	6 kV	Discharge current, max. (8/20 μ s)	3 kA
Fuse	16 A	Leakage current at U_n	30 μ A
Low voltage network	Single-phase	Mains frequency at 250 Vmax	50...60Hz
Max. continuous voltage, U_c (AC)	300 V	Number of poles	1
PE conductor current I_{PE}	30 μ A	Protection level U_p (typ.)	\leq 1200 V
Protection level U_p at I_N (L/N-PE)	\leq 1.8 kV	Rated current I_N	16 A
Rated voltage (AC)	230 V	Requirements category acc. to IEC 61643-11	Type III
Requirements class, acc. to EN 61643-11	T3	Response time	\leq 100 ns
Short-circuit current rating I_{SCCR}	1.5 kA	Signalling contact	250 V 10 A 1 NC
Temporary surge voltage (over-voltage) - TOV	438 V	Voltage type	AC

VPU series
VPU III R 230V/6KV AC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Connection data**

Type of connection	Screw connection	Stripping length, rated connection	7 mm
Tightening torque, min.	0.4 Nm	Tightening torque, max.	0.5 Nm
Clamping range, rated connection	2.5 mm ²	Clamping range, min.	0.5 mm ²
Clamping range, max.	2.5 mm ²	Wire cross-section, solid, min.	0.13 mm ²
Wire cross-section, solid, max.	2.5 mm ²	Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire connection cross section, finely stranded, max.	2.5 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	0.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	2.5 mm ²	Connection cross-section, stranded, min.	0.5 mm ²
Connection cross-section, stranded, max.	2.5 mm ²		

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
eClass 9.0	27-13-08-05	eClass 9.1	27-13-08-05
eClass 10.0	27-13-08-05	UNSPSC	30-21-19-21

Approvals

Approvals




ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	EAC VPU SERIES CE PAPER Declaration of Conformity
Brochure/Catalogue	CAT 4.4 ELECTR 16/17 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP
User Documentation	Instruction sheet

Data sheet**VPU series
VPU III R 230V/6KV AC**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Electric symbol**

Schematic circuit diagram