

TAILKITCONTRACTOR

TAILKITCONTRACTOR

Tails Kits: Plastic



Protection class IP68 (5 bar 30 min)/ IP69 K
Glow wire test 750 °C
Temperature range -40 °C - 100 °C
Material Screw Polyamide, Gasket EPDM



QUIXX Push-In (Flame Retardent)



Protection class IP66
Glow wire test 960 °C
Temperature range -40 °C - 80 °C
Material TPE, flame retardent

CLIXX



Protection class IP66 / IP67
Temperature range -40 °C - 65 °C
Material Polypropylene, Membrane TPE
Cable Retention Restraining capacity according to EN 62444

Kit Contains...

Glands: 30 x ESKV 20 plus,
10 x ESKV 32, 10 x ESKV 25
5 x TKE/P 40 Kit

Locknuts: 30 x 20mm, 10 x 32mm,
10 x 25mm

EMT-F: 20 x 20mm, 10 x 25mm,
10 x 32mm

Adaptor: 3 x KEM 32/40mm

CLIXX: 15 x 20mm

Inserts FFD: 5 x SPRINT FFD 20/01,
5 x FFD 25/01,
5 x FFD 25/02,
5 x FFD 20/02,
5 x FFD 20/01
5 x FFD 32/01/098-197

Inserts MFD: 5 x MFD 20/03/040, 5 x
MFD 20/02/060,
5 x MFD 32/01/06-02/090

Inserts RDE: 5 x RDE M20 Reduction