Product data sheet Characteristics

XB4BA821

Harmony XB4, Push button reset, metal, flush, black, Ø22, 6...16 mm actuation distance, unmarked





Main

Range of product	Harmony XB4	
Product or component type	Manual overload reset push-button	
Device short name	XB4	
Bezel material	Chromium plated metal	
Fixing collar material	Zamak	
Head type	Standard	
Mounting diameter	22 Mm	
Operator profile	Black flush, unmarked	
Activating distance	616 Mm	

Complementary

Net weight	0.037 Kg	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
Shape of signaling unit head	Round	
Operating travel	10 Mm	
Mechanical durability	5000000 Cycles	

Environment

Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	
Electrical shock protection class	Class I conforming to IEC 60536	
IP degree of protection	IP66 conforming to IEC 60529	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK03 conforming to IEC 50102	

Standards	EN/IEC 60947-5-1	
Statidatus		
	CSA C22.2 No 14	
	EN/IEC 60947-5-5	
	EN/IEC 60947-5-4	
	UL 508	
	JIS C8201-5-1	
	EN/IEC 60947-1	
	JIS C8201-1	
Product certifications	CSA	
	DNV	
	GL	
	BV	
	LROS (Lloyds register of shipping)	
	UL listed	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	42.0 G
Package 1 Height	5.3 Cm
Package 1 width	3.4 Cm
Package 1 Length	4.3 Cm
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Weight	1.485 Kg
Package 2 Height	15 Cm
Package 2 width	15 Cm
Package 2 Length	40 Cm

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope)	
Yes	
Yes	
₽	
ਊ China RoHS Declaration	
Product Environmental Profile	
☐ End Of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

Contractual warranty

Warranty	18 months

Product Life Status :	Commercialised	
i i oddot Elio Otatao .	Commission	