



### Main

|                                 |                       |
|---------------------------------|-----------------------|
| Range of product                | Harmony XB4           |
| Product or component type       | Pilot light           |
| Device short name               | XB4                   |
| Bezel material                  | Chromium plated metal |
| Fixing collar material          | Zamak                 |
| Head type                       | Standard              |
| Mounting diameter               | 22 Mm                 |
| Sale per indivisible quantity   | 1                     |
| Shape of signaling unit head    | Round                 |
| Cap/operator or lens colour     | Green                 |
| Operator additional information | With plain lens       |
| Light source                    | Bulb not included     |
| Bulb base                       | BA 9s                 |
| Light block supply              | Direct <2.4 W         |
| [Us] rated supply voltage       | <= 250 V              |

### Complementary

|  |   |
|--|---|
| Height                                 | 47 Mm   |
| Width                                  | 30 Mm   |
| Depth                                  | 55 Mm   |
| Terminals description ISO n°1          | (X1-X2)PL   |
| Net weight                             | 0.075 Kg  |
| Resistance to high pressure washer     | 7000000 Pa at 55 °C, distance : 0.1 m   |
| Connections - terminals                | Screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end conforming-<br>to EN/IEC 60947-1<br>Screw clamp terminals, 1 x 0.22...2 x 2.5 mm <sup>2</sup> without cable end conforming-<br>to EN/IEC 60947-1 |
| [Ui] rated insulation voltage          | 250 V (pollution degree 3) conforming to EN 60947-1   |
| [Uimp] rated impulse withstand voltage | 4 KV conforming to EN 60947-1   |
| Signalling type                        | Steady  |
| Device presentation                    | Complete product  |



## Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TH   |
| Ambient air temperature for storage   | -40...70 °C  |
| Ambient air temperature for operation | -40...55 °C  |
| Electrical shock protection class     | Class I conforming to IEC 60536  |
| IP degree of protection               | IP66 conforming to IEC 60529<br>IP67<br>IP69<br>IP69K  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X   |
| IK degree of protection               | IK06 conforming to IEC 50102   |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-5<br>EN/IEC 60947-1<br>UL 508<br>JIS C8201-1  |
| Product certifications                | UL listed<br>CSA   |
| Vibration resistance                  | 5 gn (f= 12...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Weight             | 74.0 G    |
| Package 1 Height             | 3.4 Cm    |
| Package 1 width              | 5.4 Cm    |
| Package 1 Length             | 8.8 Cm    |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 150       |
| Package 2 Weight             | 11.657 Kg |
| Package 2 Height             | 30 Cm     |
| Package 2 width              | 30 Cm     |
| Package 2 Length             | 40 Cm     |
| Unit Type of Package 3       | BB1       |
| Number of Units in Package 3 | 5         |
| Package 3 Weight             | 1.37 Kg   |
| Package 3 Height             | 3.4 Cm    |
| Package 3 width              | 8.8 Cm    |
| Package 3 Length             | 26.5 Cm   |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           |  <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information |  <a href="#">Yes</a>  |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>   |

|                           |   |
|---------------------------|---|
| Environmental Disclosure  | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile       | <a href="#">End Of Life Information</a>   |
| WEEE                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

|                       |                       |
|-----------------------|-----------------------|
| Product Life Status : | <b>Commercialised</b> |
|-----------------------|-----------------------|