



### Main

|                               |  |
|-------------------------------|--|
| Range of product              | Harmony XB5  |
| Product or component type     | Complete selector switch   |
| Device short name             | XB5F   |
| Bezel material                | Dark grey plastic  |
| Head type                     | Built-in-flush   |
| Mounting diameter             | 30.5 mm  |
| Sale per indivisible quantity | 1  |
| Shape of signaling unit head  | Round  |
| Type of operator              | Stay put   |
| Operator profile              | Black standard handle unmarked   |
| Operator position information | 3 positions +/- 45°  |
| Contacts type and composition | 2 NO   |
| Contact operation             | Slow-break   |
| Connections - terminals       | Screw clamp terminals : $\leq 2 \times 1.5 \text{ mm}^2$ with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals : $>= 1 \times 0.22 \text{ mm}^2$ without cable end conforming to EN/IEC 60947-1 |

### Complementary

|                                    |   |
|------------------------------------|---|
| Height                             | 42 mm   |
| Width                              | 36.6 mm   |
| Depth                              | 73 mm   |
| Terminals description ISO n°1      | (13-14)NO<br>(23-24)NO  |
| Resistance to high pressure washer | 7000000 Pa at 55 °C, distance: 0.1 m  |
| Contacts usage                     | Standard contacts   |
| Positive opening                   | Without positive opening  |
| Mechanical durability              | 1000000 cycles  |
| Tightening torque                  | 0.8...1.2 N.m conforming to EN 60947-1  |
| Shape of screw head                | Cross head compatible with Philips no 1 screwdriver<br>Cross head compatible with pozidriv No 1 screwdriver<br>Slotted head compatible with flat Ø 4 mm screwdriver<br>Slotted head compatible with flat Ø 5.5 mm screwdriver |
| Contacts material                  | Silver alloy (Ag/Ni)  |
| Short-circuit protection           | 10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1  |

|   |  |
|---|--|
| [Ith] conventional free air thermal current | 10 A conforming to EN/IEC 60947-5-1  |
| [Ui] rated insulation voltage               | 600 V (degree of pollution: 3) conforming to EN 60947-1  |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to EN 60947-1  |
| [Ie] rated operational current              | 1.2 A 600 V AC-15 A600 EN/IEC 60947-5-1<br>0.27 A 250 V DC-13 Q600 EN/IEC 60947-5-1<br>0.1 A 600 V DC-13 Q600 EN/IEC 60947-5-1<br>3 A 240 V AC-15 A600 EN/IEC 60947-5-1<br>0.55 A 125 V DC-13 Q600 EN/IEC 60947-5-1<br>6 A 120 V AC-15 A600 EN/IEC 60947-5-1   |
| Electrical durability                       | 1000000 cycles, AC-15, 2 A at 230 V, operating rate: <= 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles, AC-15, 3 A at 120 V, operating rate: <= 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles, AC-15, 4 A at 24 V, operating rate: <= 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13, 0.2 A at 110 V, operating rate: <= 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13, 0.5 A at 24 V, operating rate: <= 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C |
| Electrical reliability                      | $\Lambda < 10\exp(-6)$ at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4<br>$\Lambda < 10\exp(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4  |
| Device presentation                         | Complete product   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TH   |
| Ambient air temperature for storage   | -40...70 °C  |
| Ambient air temperature for operation | -40...70 °C  |
| Electrical shock protection class     | Class II conforming to IEC 60536   |
| IP degree of protection               | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X   |
| IK degree of protection               | IK03 conforming to IEC 50102   |
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>JIS C 4520<br>EN/IEC 60947-1<br>UL 508  |
| Product certifications                | CSA<br>UL listed   |
| Vibration resistance                  | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

## Offer Sustainability

|                        |   |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1804 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                  | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|