# Product data sheet Characteristics

# **ZB4BW36**

Harmony XB4, Illuminated push button head, metal, flush, blue, Ø22, spring return, plain lens for BA9s bulb





#### Main

Range of product	Harmony XB4
Product or component type	Head for illuminated push-button
Device short name	ZB4
Product compatibility	BA 9s
Bezel material	Chromium plated metal
Head type	Standard
Mounting diameter	22 Mm
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Blue flush, unmarked
Operator additional information	With plain lens

## Complementary

CAD overall width	29 Mm
CAD overall height	29 Mm
CAD overall depth	32 Mm
Net weight	0.027 Kg
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m
Mechanical durability	10000000 Cycles
Electrical composition code	M7 for <6 contacts using single blocks in front mounting with BA 9s M8 for <6 contacts using single and double blocks in front mounting with BA 9s M9 for <2 contacts using single blocks in front mounting with BA 9s and transformer
Device presentation	Basic sub-assemblies

#### **Environment**

Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4055 °C	
Overvoltage category	Class I conforming to IEC 60536	
IP degree of protection	IP66 conforming to IEC 60529 IP67 IP69 IP69K	

NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK06 conforming to EN 50102
Standards	EN/IEC 60947-1 JIS C8201-5-1 EN/IEC 60947-5-1 CSA C22.2 No 14 UL 508 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C8201-1
Product certifications	DNV GL BV LROS (Lloyds register of shipping) CSA UL listed
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming- to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming- to IEC 60068-2-27

# Packing Units

. c.c.m.g c.m.c		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	26.0 G	
Package 1 Height	4.5 Cm	
Package 1 width	3.4 Cm	
Package 1 Length	5.4 Cm	
Unit Type of Package 2	S01	
Number of Units in Package 2	50	
Package 2 Weight	1.527 Kg	
Package 2 Height	15 Cm	
Package 2 width	15 Cm	
Package 2 Length	40 Cm	

## Offer Sustainability

oner cuctamasmy	
Sustainable offer status	Green Premium product
REACh Regulation	<sup>™</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information

# Contractual warranty

Warranty 18 months

Product Life Status : Commercialised

