Product data sheet Characteristics

ZB5AD912

Harmony XB5, Potentiometer head, plastic, black, Ø22, for use with Ø 6 mm shaft





Main

Range of product	Harmony XB5	
Product or component type	Head + mounting base for potentiometer	
Device short name	ZB5	
Bezel material	Dark grey plastic	
Mounting diameter	22 Mm	
Head type	Standard	
Product compatibility	For use with Ø 6 mm shaft	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Operator profile	Knurled knob, with (white)	

Complementary

Net weight	0.032 Kg
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m
Device presentation	Basic element

Environment

Liviloriment	
Protective treatment	TH
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-4070 °C
Electrical shock protection class	Class II conforming to IEC 60536
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK03 conforming to IEC 50102
Standards	JIS C8201-5-1 EN/IEC 60947-1 EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-4 EN/IEC 60947-5-5 CSA C22.2 No 14 JIS C8201-1
Product certifications	GL LROS (Lloyds register of shipping) UL listed CSA DNV BV

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interneted as a substitute for and is not to be used for determining suitability or reliability of these products with expect to the relevant specific application it is the douty of any sub user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or substitiaries shall be responsible or liable for misuse of the information contained herein.

Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming- to IEC 60068-2-27
	50 gn (duration = 11 ms) for half sine wave acceleration conforming- to IEC 60068-2-27

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	33.375 G
Package 1 Height	4.5 Cm
Package 1 width	5.5 Cm
Package 1 Length	5.5 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	80
Package 2 Weight	2.963 Kg
Package 2 Height	15 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
Yes
₫Yes
☑ China RoHS Declaration
Product Environmental Profile
☑ End Of Life Information
WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Product Life Status : Commercialised

