Product data sheet Characteristics

ZB5FK1333

flush mounted white illuminated selector switch head 3 pos stay put





Main

| IVICIII | | ç |
|-------------------------------|--------------------------------------|----------|
| Range of product | Harmony XB5 | |
| Product or component type | Head for illuminated selector switch | Ť |
| Product compatibility | Integral LED | |
| Device short name | ZB5 | |
| Bezel material | Dark grey plastic | |
| Mounting diameter | 30 mm | <u></u> |
| Head type | Built-in-flush | |
| Sale per indivisible quantity | 1 | <u> </u> |
| Shape of signaling unit head | Round | |
| Type of operator | Stay put | |
| Operator profile | Green standard handle | |
| Operator position information | 3 positions +/- 45° | |
| | | |

Complementary

| CAD overall width | 37 mm | |
|-----------------------------|--|-----------|
| CAD overall height | 37 mm | |
| CAD overall depth | 46 mm | |
| Product weight | 0.03 kg | |
| Mechanical durability | 1000000 cycles | |
| Electrical composition code | M6 for 2 contacts using single blocks in front mounting with integral LED and transformer M10 for 2 contacts using single blocks in front mounting with integral LED M3 for 4 contacts using single blocks in front mounting with integral LED M4 for 4 contacts using single and double blocks in front mounting with integral LED MF1 for 2 contacts using single blocks in front mounting with integral LED | oi coi |

Environment

| | | .= |
|-------------------------------------|----------|----|
| Protective treatment | TH | _; |
| Ambient air temperature for storage | -4070 °C | |
| · | | |

| Ambient air temperature for operation | -4070 °C |
|---------------------------------------|---|
| Overvoltage category | Class II conforming to IEC 60536 |
| IP degree of protection | IP69 IP67 IP66 conforming to IEC 60529 IP69K |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| Resistance to high pressure washer | 7000000 Pa at 55 °C,distance: 0.1 m |
| IK degree of protection | IK03 conforming to IEC 50102 |
| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14 |
| Product certifications | BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed |
| Vibration resistance | 5 gn (f = 2500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------------|---|--|
| RoHS (date code: YYWW) | Compliant - since 1804 - Schneider Electric declaration of conformity | |
| | Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| | Reference not containing SVHC above the threshold | |
| Product environmental profile | Available | |
| Product end of life instructions | Available | |