

## Commercial Specification Grade Straight Blade Receptacles

2-Pole, 3-Wire Grounding  
15A, 125V/AC  
NEMA 5-15R



5-15R

### Clock Hanger Receptacle

#### FEATURES

- Single receptacle on recessed wallplate with integral hook.
- High impact- and chemical-resistant nylon face.
- 0.035" (8.73mm) galvanized steel wrap-around yoke mounting strap for superior assembly security.
- Tamper Resistant to comply with 2008 NEC®.

#### Tamper Resistant NEMA 5-15R, Back Wire & Side Wire



Rating	A	V/AC	Description	Color	Catalog No.	
15	125		Single Clock Hanger Receptacle with Wallplate	W	□ TR775	




### Snap-In Receptacles

#### Large Face NEMA 5-15R




Rating	A	V/AC	Description	Color	Catalog No.	
15	125		Single Receptacle, Plastic Back & Clips, Quick Connect with Screw Terminal Grounding	Black	□ 4067BK	•
			Single Receptacle, Fiber Back & Steel Clips, Quick Connect with Screw Terminal Grounding	Black	□ 4067-01BK	•
			Duplex Receptacle, Plastic Back & Clips, Solder Connect, Slotted Terminals	Black	□ 4070-6BK	•



#### Rectangular NEMA 5-15R



Rating	A	V/AC	Description	Color	Catalog No.	
15	125		Single Receptacle, Plastic Back & Clips, Quick Connect with Screw Terminal Grounding	Black	□ 67BK	•
			Single Receptacle, Plastic Back & Clips, Quick Connect with Screw Terminal Grounding	White	□ 67W	•
			Single Receptacle, Plastic Back & Clips, Quick Connect with Wire Lead Grounding	Black	□ 67-2BK	•
			Single Receptacle, Plastic Back & Clips, Quick Connect with Wire Lead Grounding	White	□ 67-2W	•
			Plug, Solder Connect, Slotted Terminals	Black	□ 4049BK*	•



\* Not NOM

### Color Ordering Information

For ordering receptacles, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), BL (Blue), GY (Gray), LA (Light Almond), RD (Red), RN (Orange), V (Ivory), W (White)

### Icon Key

- NAFTA Compliant - see page O-30
- Tamper Resistant

### Specification Information:

Snap-In Commercial Receptacles: A-36