

Bahco wrenches and spanners
Ega Master adjustable wrenches
Gedore adjustable wrenches



Repair Management Nederland B.V.
 More management less firefighting

**80 series phosphated and protected against corrosion
 DIN 3117 Form A**

Number	Description	Opening
300101	4 1/4 inch. 110 mm. 8069	13 mm
300102	6 inch. 155 mm. 8070	20 mm
300103	8 inch. 205 mm. 8071	27 mm
300104	10 inch. 255 mm. 8072	30 mm
300106	12 inch. 305 mm. 8073	34 mm
300107	15 inch. 380 mm. 8074	44 mm
300108	18 inch. 455 mm. 8075	53 mm



90 series with comfortable thermoplastic handle and protected against corrosion

Number	Description	Opening
300120	6 inch. 155 mm. 9070 Ergo	20 mm
300121	8 inch. 208 mm. 9071 Ergo	27 mm
300122	10 inch. 257 mm. 9072 Ergo	30 mm
300123	12 inch. 308 mm. 9073 Ergo	34 mm



90 series type P with reversible jaw to use spanner as a pipe wrench

Number	Description	Opening
300148	6 inch. 155 mm. 9070P	20 mm
300149	8 inch. 208 mm. 9071P	27 mm
300150	10 inch. 257 mm. 9072P	30 mm
300151	12 inch. 308 mm. 9073P	34 mm



80 series phosphated and protected against corrosion.

Number	Description	Opening
300190	Bahco 86 length 614 mm	63 mm
300191	Bahco 87 length 770 mm	85 mm



**90 series phosphated and protected against corrosion.
 With 40% bigger jaw as normal.**

Number	Description	Opening
300130	Bahco 9029 length 170mm	32mm
300132	Bahco 9031 length 214mm	38mm
300134	Bahco 9033 length 270mm	46,5mm
300136	Bahco 9035 length 324mm	55,6mm



Spare parts for Bahco adjustable wrenches

Number	Description	Number	Description
300200	Roll, pin and spring for 8069	300207	Jaw for 8072
300201	Jaw for 8069	300208	Roll, pin and spring for 8073
300202	Roll, pin and spring for 8070	300209	Jaw for 8073
300203	Jaw for 8070	300210	Roll, pin and spring for 8074
300204	Roll, pin and spring for 8071	300211	Jaw for 8074
300205	Jaw for 8071	300212	Roll, pin and spring for 8075
300206	Roll, pin and spring for 8072	300213	Jaw for 8075



Ega Master adjustable wrench Titacrom® Comfort

Fitted with a thermoplastic comfort grip

Number	Length	Opening
24E61906	6" - 150mm	19mm
24E61907	8" - 200mm	24mm
24E61908	10" - 250mm	29mm
24E61909	12" - 300mm	33mm
24E61370	15" - 375mm	45mm
24E61371	18" - 450mm	55mm
24E61372	24" - 600mm	62mm

**Ega Master adjustable wrench Titacrom® standard**

Number	Length	Opening
24E61109	4" - 100mm	13mm
24E61110	6" - 150mm	19mm
24E61111	8" - 200mm	24mm
24E61112	10" - 250mm	29mm
24E61113	12" - 300mm	33mm
24E61114	15" - 375mm	45mm
24E61115	18" - 450mm	55mm
24E61116	24" - 600mm	60mm
24E62980	30" - 750mm	85mm

**Ega Master adjustable wrench Titacrom® 1000V**

Fitted with double hard-soft PVC insulation for maximum adherence and safety

Number	Length	Opening
24E76550	6" - 150mm	19mm
24E76551	8" - 200mm	24mm
24E76552	10" - 250mm	29mm
24E76553	12" - 300mm	33,5mm

**Ega Master adjustable wrench Titacrom® Wide opening (plumbing)**

With an extra wide opening.

Number	Length	Opening
24E61229	6" - 150mm	35mm
24E61213	8" - 200mm	41mm

**Ega Master adjustable wrench Titacrom® Comfort wide opening (plumbing)**

With an extra wide opening.

Fitted with a thermoplastic comfort grip

Number	Length	Opening
24E61230	6" - 150mm	35mm
24E61214	8" - 200mm	41mm

**Ega Master adjustable wrench Titacrom® Comfort reverse jaw**

Fitted with a thermoplastic comfort grip

With reversible and movable jaw to use on nuts and pipes

Number	Length	Opening
24E61944	10" - 250mm	29mm
24E61945	12" - 300mm	33mm

**Ega Master adjustable wrench Titacrom® Standard reverse jaw**

With reversible and movable jaw to use on nuts and pipes

Number	Length	Opening
24E61942	10" - 250mm	29mm
24E61943	12" - 300mm	33mm



Ega Master adjustable wrench Titacrom® 1000V reverse jaw

Fitted with double hard-soft PVC insulation for maximum adherence and safety
With reversible and movable jaw to use on nuts and pipes

Number	Length	Opening
24E76562	10" - 250mm	29mm
24E76563	12" - 300mm	33mm



Ega Master adjustable wrench Titacrom® Comfort reverse jaw extra wide (plumbing)

Fitted with a thermoplastic comfort grip
With reversible and movable jaw to use on nuts and pipes

Number	Length	Opening
24E61238	8" - 200mm	41mm



Ega Master adjustable wrench Titacrom® Comfort with lateral nut

Fitted with a thermoplastic comfort grip
With lateral turning knob (nut) for extra adjusting force

Number	Length	Opening
24E61061	8" - 200mm	24mm
24E61062	10" - 250mm	29mm
24E61063	12" - 300mm	33mm



Ega Master adjustable wrench Titacrom® 1000V with lateral nut

Fitted with double hard-soft PVC insulation for maximum adherence and safety
With lateral turning knob (nut) for extra adjusting force

Number	Length	Opening
24E76578	6" - 150mm	19mm
24E76579	8" - 200mm	24mm
24E76580	10" - 250mm	29mm
24E76581	12" - 300mm	33mm



Ega Master adjustable structural wrench

With pogging pin for construction work.
For construction, windmill installation, flange mounting.

Number	Length	Opening
24E61137	16" - 400mm	42mm



Gedore adjustable wrench phosfated Type 60P -62P

Size 6" - 18" = DIN 3117 Shape A, jaw angle = 15°
Size 24" = DIN 3117 Shape B, Jaw angle = 22,5°
Swedish model, roll is left turning.

Number	Length	Opening	
2360P06	6"	155 mm	20

Number	Length	Opening
--------	--------	---------

2360P08	8"	205 mm	25
2360P10	10"	255 mm	30
2360P12	12"	305 mm	36
2362P15	15"	380 mm	43
2362P18	18"	455 mm	53
2362P24	24"	610 mm	63

