



Sample photo

**Order symbol:** MCE ISO 14 P/P  
**Product nbr:** 7231314  
**Description:** DIN rail modular enclosure  
**Remarks:**

**EAN:** 6418074008138  
**EI. number:**  
 Finland 3422239  
 Denmark 8212029224  
 Italy 7760140

**Including:** Modular component enclosure with TPE gaskets, mounted DIN 35-rail, wall mount cover plugs and mounting instructions. PC/FEM only: two PEN 10 mm<sup>2</sup> bars mounted, Multi-FEM and FEM membrane cable glands, module marking stripe and pocket.

Dimensions:	L	W	H
mm:	280	306	145
inch:	11	12	5.7

**Materials:**

<b>Material:</b>	PS
<b>Base colour:</b>	RAL 7035
<b>Cover colour:</b>	Smoked grey
<b>Cover screws material:</b>	Polyamide
<b>Cover screws colour:</b>	Grey
<b>Gasket material:</b>	TPE

**Temperatures:**

<b>Short term:</b>	-30 ... 80 °C
<b>Continuous:</b>	-30 ... 60 °C
<b>Short term:</b>	-22 ... 175 °F
<b>Continuous:</b>	-22 ... 140 °F

**Accessories:**

PEN 16x10	PEN-bar for MCE 14
PEN 35x10	PEN-bar for MCE 28+
PEN H 26140	PEN-bar holder for MCE 14+
MCE 14 PEN SET	Mounting ready PE/N/PEN -rail set
MCE MU PEN SET	Multiadapter set
FP 26128	Fastening lug set
FP 26127	Fastening lug set
FP A 26133	Front plate
MR 26065	Key lock set

**Rating:**

<b>Ingress Protection (EN 60529):</b>	IP 55
<b>Impact Resistance (EN 50102):</b>	IK 07
<b>Electrical insulation:</b>	Totally insulated
<b>Halogen free (DIN/VDE 0472, Part 815):</b>	Yes
<b>Flammability Rating (UL 746 C 5):</b>	UL 94 HB
<b>Glow Wire Test (IEC 695-2-1) °C:</b>	750

**Certificates:**

