

ARCA 608030F



Order symbol: ARCA 608030F
Product nbr: 8120269
Description:
Remarks:

EAN: 6418074085306
EI. number:
Finland: 3424080
Denmark: 8212095520
Sweden: 2500135
Norway:

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key.
S versions with swinghandle 3-point locking system. F versions with flange opening. Door guide included.

Sample photo

| Dimensions: | | Length | Width | Height | Rating: |
|-------------------------|--|---------------------------|-------|--------|--|
| mm: | | 600 | 800 | 300 | Ingress Protection (EN 60529): IP 66 |
| inch: | | 23.6 | 31.5 | 11.8 | Impact Resistance (EN 62262): IK 10 +35°C /IK 08 -25°C |
| Materials: | | | | | Electrical insulation: Totally insulated |
| Material: | | Polycarbonate | | | Halogen free (DIN/VDE 0472, Part 815): Yes |
| Base colour: | | RAL 7035 | | | UV resistance: UL 508 |
| Cover colour: | | RAL 7035 | | | Glow Wire Test (IEC 695-2-1) °C: 960 |
| Gasket material: | | PUR | | | Certificates: |
| Temperatures: | | | | | SGS Fimko |
| Short term: | | -40 ... 120 °C | | | |
| Continuous: | | -40 ... 80 °C | | | |
| Short term: | | -40 ... 250 °F | | | |
| Continuous: | | -40 ... 175 °F | | | |
| Accessories: | | | | | |
| MPP ARCA 8060 | | Mounting plate perforated | | | |
| MPS ARCA 8060 | | Mounting plate | | | |
| MPX ARCA 8060 | | Mounting plate | | | |
| IDS ARCA 6080 | | Inner door set | | | |
| PMK ARCA 80 | | Pole mounting kit | | | |

