

PRODUCT SPECIFICATION

**Carl
Kammerling**
International

Brand	C.K
Product Range	Dextro VDE Slim Screwdrivers
Catalogue number	49242, 49243, 49244, 49245, 49283
Date	02/02/2017

Range Description

A range of slim shafted VDE approved professional Electricians screwdrivers

Features

- Slim shafted insulated blades - allow access to recessed screws and fixings
- Optimised grip for fingertip control and final torque down power
- Non-roll handle design – specifically designed to stop the screwdrivers rolling off non-flat surfaces
- Permanent tip type marking on the end of the handle for convenient blade type identification
- Additional blade type identification with colour coded handles
- Toughened high alloy steel blade offering the ultimate in wear resistance and performance
- Blade torque capacity up to 20% over the International standards requirement
- Chrome vanadium blade with black non peel tip finish for corrosion protection
- Precision machined tips for the ultimate screw fit and high torque output



T49242



T49243



T49244



T49245



T49283

PRODUCT SPECIFICATION

Brand	C.K
Product Range	Automatic Wire Strippers
Catalogue number	950
Date	24/11/2006

<p>Range Description Automatic wire strippers.</p>	
<p>Features</p> <ul style="list-style-type: none"> • Fast single action automatic wire stripper • Automatic stripping of PVC sheathed cables – fast and damage free stripping of outer and inner insulation in just two passes • Automatically adjusts to size for the ultimate in convenience • Depth stop for fixed stripping lengths – convenient in first fix applications • Micro adjustment facility allows wires smaller than 0.2mm to be stripped • Hardened steel blades for long life operation • Convenient crimping facility for both insulated and non insulated terminals • Wire cutter facility – no need for additional tools 	



Item Number	Item Description	EAN No	Commodity code	Carton Qty
495001	Automatic Wire Stripper	5051074950017	82032090	3

Technical product information	<p>Body – steel Handles – ABS Plastic Stripping Jaws – Hardened steel</p> <p>Capacities: Strips up to 6.0mm² Copper or Aluminium cored wire, solid or stranded, micro adjustment facility for wires below 0.2mm² Cuts wire with a hardness up to 50 HRC Crimps 1.5, 2.5 and 6mm insulated terminals (Yellow, Red and Blue) Crimps 1.5, 2.5, 4 & 6mm non-insulated terminals Crimps non-insulated spades</p>
Standards compliance	None applicable
User health and safety information	None applicable
RoHS/WEEE compliance	This product range does not fall within the scope of RoHS or WEEE regulations
Material safety data	None applicable
Warranty	<p>The Automatic Wire strippers are guaranteed for life against imperfect materials or workmanship The strippers contain moving parts that may wear over time, these are not covered under the terms of the warranty</p>
Country of origin	Taiwan

Dimensional details

Item	Product only				Product on primary packaging			
	Width mm	Depth mm	Height mm	Net weight g	Width mm	Depth mm	Height mm	Gross weight g
495001	100	25	205	309	120	35	265	355

Item	Shelf box (secondary packaging)				Euro Pallet data Wi x Hi	
	Width mm	Depth mm	Height mm	Gross weight g	No of cartons on base	Number of rows high
495001	140	290	85	1175	20	13

Packaging waste details

Item	Primary Packaging				Secondary packaging			
	Plastic g	Use	Card g	Use	Plastic g	Use	Card g	Use
496001	22	Blister	24	Backing card			110	Box

Code	
T49242-1	DextroVDE Slim S/Driver PH1x100
T49242-2	DextroVDE Slim S/Driver PH2x125
T49243-1	DextroVDE Slim S/Driver PZ1x100
T49243-2	DextroVDE Slim S/Driver PZ2x125
T49244-035	DextroVDE Slim S/Driver SLP 3.5x100
T49244-040	DextroVDE Slim S/Driver SLP 4.0x100
T49244-055	DextroVDE Slim S/Driver SLP 5.5x125
T49245-2	DextroVDE Slim S/Driver MOD2x125
T49283	DextroVDE Slim S/Driver SLP/PZD Set/5 contains SL3.5x100, SL4.0x100, SL5.5x125, PZ1x100, PZ2x125

<p>Technical product information</p>	<p>Blade/Shaft</p> <p>Made from chrome molybdenum vanadium steel, hardened to 57-59 HRC, black non peel finish.</p> <p>Handle</p> <p>The handle core is polypropylene, injection moulded around the blade with a TPE soft grip over-mould. The handles are shatterproof down to -35° C.</p> <p>Dimensions</p> <table border="1" data-bbox="488 1018 1252 1371"> <thead> <tr> <th>Dimensions (mm)</th> <th>Handle length</th> <th>Blade length</th> <th>Blade Dia</th> <th>Tip thickness</th> </tr> </thead> <tbody> <tr> <td>T49242-1</td> <td>95</td> <td>100</td> <td>5.5</td> <td>-</td> </tr> <tr> <td>T49242-2</td> <td>107</td> <td>125</td> <td>6.5</td> <td>-</td> </tr> <tr> <td>T49243-1</td> <td>95</td> <td>100</td> <td>4.5</td> <td>-</td> </tr> <tr> <td>T49243-2</td> <td>107</td> <td>125</td> <td>6.5</td> <td>-</td> </tr> <tr> <td>T49244-035</td> <td>95</td> <td>100</td> <td>3.5</td> <td>0.6</td> </tr> <tr> <td>T49244-040</td> <td>95</td> <td>100</td> <td>4</td> <td>0.8</td> </tr> <tr> <td>T49244-055</td> <td>107</td> <td>125</td> <td>5.5</td> <td>1.0</td> </tr> <tr> <td>T49245-2</td> <td>107</td> <td>125</td> <td></td> <td>-</td> </tr> </tbody> </table>	Dimensions (mm)	Handle length	Blade length	Blade Dia	Tip thickness	T49242-1	95	100	5.5	-	T49242-2	107	125	6.5	-	T49243-1	95	100	4.5	-	T49243-2	107	125	6.5	-	T49244-035	95	100	3.5	0.6	T49244-040	95	100	4	0.8	T49244-055	107	125	5.5	1.0	T49245-2	107	125		-
Dimensions (mm)	Handle length	Blade length	Blade Dia	Tip thickness																																										
T49242-1	95	100	5.5	-																																										
T49242-2	107	125	6.5	-																																										
T49243-1	95	100	4.5	-																																										
T49243-2	107	125	6.5	-																																										
T49244-035	95	100	3.5	0.6																																										
T49244-040	95	100	4	0.8																																										
T49244-055	107	125	5.5	1.0																																										
T49245-2	107	125		-																																										
<p>Standards compliance</p>	<p>Electrical safety</p> <p>Fully approved and independently audited by the German VDE institute to VDE 0682/201:2005 01 IEC 60900:2012</p> <p>Dimensional and performance</p> <p>Slotted screwdrivers – DIN ISO 2380 PZD/SDV/PH Screwdrivers – DIN ISO 8764</p>																																													
<p>User health and safety information</p>	<p>Users and bystanders are advised to wear safety goggles</p>																																													
<p>RoHS/WEEE compliance</p>	<p>This product range does not fall within the scope of RoHS or WEEE regulations</p>																																													

Material safety data	None applicable
Warranty	Dextro Screwdrivers are guaranteed for life against imperfect materials or workmanship Normal wear and tear or damage caused through inappropriate use is not covered
Country of origin	Germany

Dimensional details

Product only				
Item	Width mm	Depth mm	Height mm	Net weight g
T49242-1	30	25	195	46
T49242-2	35	30	232	74
T49243-1	30	25	195	46
T49243-2	35	30	232	80
T49244-035	30	25	195	39
T49244-040	30	25	195	43
T49244-050	35	30	232	74
T49245-2	35	30	232	80
T49283	225	43	300	635