

CAB CAB P 1008030



Sample photo

Order symbol: CAB P 1008030
Product nbr: 8104309
Description: Polyester cabinet
Remarks: Grey door

EAN: 6418074050069
El. number:
 Finland: 3424145
 Denmark: 8212018060
 Sweden: 2539829
 Norway:

Including: Cabinet base, door with PUR gasket, 3mm double bit lock(s) with transport and plastic key.

Dimensions:		Length	Width	Height	Rating:
mm:		1035	835	300	Ingress Protection (EN 60529): IP 66
inch:		40.7	32.9	11.8	Impact Resistance (EN 62262): IK 10
Materials:					Electrical insulation: Totally insulated
Material:		Polyester		UV resistance: UL 508	
Base colour:		RAL 7035		Flammability Rating (UL 746 C 5): UL 94 HB	
Cover colour:		RAL 7035		Glow Wire Test (IEC 695-2-1) °C: 960	
Gasket material:		Polyurethane		UL Type: UL TYPE 3, 3R, 3S, 4, 4X, 12, 13	
Temperatures:					Certificates:
Short term:		-50 ... 160 °C		Gost R	
Continuous:		-40 ... 80 °C			
Short term:		-60 ... 320 °F			
Continuous:		-40 ... 176 °F			
Accessories:					
MP 10080		Mounting plate			
FP 10080-D		Swing door/Front plate			
MB CAB		Swing door kit			
MPP 10080		Mounting Plate			
MPX 10080		Mounting Plate			
MF10080		Mounting Frame with DIN-rails			
FP 10080-5x36		Front Plate with DIN openings			

