



CONI

Integrated functionality

CONI built-in frame, short and long version

Built-in depth is 56 mm, suitable for desk or table top thicknesses of 10 mm and above.

The R5 corner radius facilitates flush mounting in desks or tables.

The brush strips can easily be replaced with colour strips; no tools are required. Simply remove the built-in frame from the top of the desk or table and unscrew the 3 re-usable plastic rivets.



CONI built-in frame short

Outer dimensions: approx. 248 x 151 mm

CONI built-in frame long

Outer dimensions: approx. 386.5 x 151 mm

Art. no. | Version

CONI short Silver grey

338.0203 | · Silver-grey similar to RAL9006

CONI long Silver grey

338.0205 | · Silver-grey similar to RAL9006

CONI short Anthracite

338.0204 | · Anthracite

CONI long Anthracite

338.0206 | · Anthracite

CONI short Chrome-plated

338.0214 | · Chrome-plated

CONI long Chrome-plated

338.0227 | · Chrome-plated

CONI short Satin white

911.000 | · Satin white RAL9010

CONI long Satin white

911.001 | · Satin white RAL9010

CONI short Black

911.002 | · Black RAL9005

CONI long Black






911.003 | · Black RAL9005

CONI short Stainless steel

911.004 | · Ground stainless steel

CONI long Stainless steel

911.005 | · Ground stainless steel



CONI bracket

- For mounting CONI power strips without using a built-in frame, can be installed e.g. under a desk or table top in a cable tray. Standard spax screws (which can be purchased from all good retailers) are required for mounting.
- Takes account of the rear-side outlet and bending radii of power and data connections.

Art. no. | Version

CONI mounting high

918.002	<ul style="list-style-type: none"> · Black · 2 pcs in plastic bag · Distance between socket outlet profile and floor: 30 mm from floor to top edge · Power strip: 74 mm
---------	---



CONI holder

- For optional mounting on CONI mounting frame (short and long version)
- Allows excess lengths of cable to be stowed when plugged in
- Easy to fit by hooking into mounting frame already fitted, using plastic rivets supplied.
- Small extra built-in depth of approx. 20 mm in addition to depth of mounting frame



Art. no. | Version

CONI holder

911.910	· Version for Coni mounting frame, short
911.913	· Version for Coni mounting frame, long



CONI brushes

Art. no. | Version

CONI brush strip short

911.900	· Red
911.901	· Blue
911.902	· White
911.903	· Yellow
911.904	· Black

CONI brush strip long






911.905	· Red
911.906	· Blue
911.907	· White
911.908	· Yellow
911.909	· Black












3-way power strips for CONI



Power cables and custom modules are available separately. See glossary for country-specific information.



Art. no. | Version


	CUSTOM	3-way: 2 x custom modules + power socket outlet	Length: approx. 217 mm
	Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
		912.002	· 1 socket outlet with earthing contact, child-proof, black, set at 35°
		912.009	· 1 French / UTE socket outlets, child-proof, black, set at 35°
		912.016	· 1 Swiss / CH socket outlet, black, set at 0°
	9120055*	· 1 Italian / earth contact combination, black, set at 35°	

	CUSTOM	3-way: 1 x custom module + power socket outlets	Length: approx. 217 mm
	Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
		912.003	· 2 socket outlets with earthing contact, black, set at 35°
		912.010	· 2 French / UTE socket outlets, child-proof, black, set at 35°
		912.015	· 3 Swiss / CH socket outlets, black, set at 0°
	912.037*	· 1 socket outlet with earthing contact, black, set at 35°	
		· 1 Swiss / CH socket outlet, black, set at 0°	
	912.045*	· 2 UK 3.15A individually fused, child-proof, black, set at 90°	





	CUSTOM	3-way: 1 x custom module + power socket outlets, black and red	Length: approx. 217 mm
	Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)		
	912.023*	· 1 socket outlet with earthing contact, black, set at 35° · 1 socket outlet with earthing contact, red, set at 35°	

		3-way: 2 x CAT5e + power socket outlets	Length: approx. 217 mm
	Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
	3331008	· 2 socket outlets with earthing contact, black, set at 35° · 2 CAT5e RJ45, front: socket / rear: socket	

		3-way: Power socket outlets	Length: approx. 217 mm
	Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
	333.1007	· 3 socket outlets with earthing contact, black, set at 35°	

	CUSTOM	3-way: 3 x custom modules	Length: approx. 217 mm
	Anodised aluminium profile; without power connection		
	912.000	without socket outlets	

Art. no. | Version

	USB CHARGER	CUSTOM	3-way: 1 x USB double charger + custom modules + power socket outlets	Length: approx. 217 mm
	Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
		912.0167	· 1 socket outlet with earthing contact, child-proof, black, set at 35° · 1 x USB double charger (5.2V/2.15A), 1 x custom module	
		9120156	· 2 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger	
	912.0171	· 1 French / UTE socket outlet, child-proof, black, set at 35° · 1 x USB double charger, 1 x custom module		

* No storage type

6-way power strips for CONI

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no.	Version		
6-way: 5 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.004	· 1 socket outlet with earthing contact, child-proof, black, set at 35°		
6-way: 4 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.005	· 2 socket outlets with earthing contact, child-proof, black, set at 35°		
912.011	· 2 French / UTE socket outlets, child-proof, black, set at 35°		
912.017	· 3 Swiss / CH socket outlets, black, set at 0°		
912.0125*	· 1 UK 3.15A individually fused, child-proof, black, set at 45°		
6-way: 3 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.006	· 3 socket outlets with earthing contact, child-proof, black, set at 35°		
912.012	· 3 French / UTE socket outlets, child-proof, black, set at 35°		
912.018	· 4 Swiss / CH socket outlets, black, set at 0°		
912.022*	· 3 UK 3.15A individually fused, child-proof, black, set at 90°		
912.0124*	· 2 UK 3.15A individually fused, child-proof, black, set at 45°		
6-way: 2 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.007	· 4 socket outlets with earthing contact, child-proof, black, set at 35°		
912.013	· 4 French / UTE socket outlets, child-proof, black, set at 35°		
912.019	· 5 Swiss / CH socket outlets, black, set at 0°		
912.035*	· 1 socket outlet with earthing contact, black, set at 35°		
	· 3 Swiss / CH socket outlets, black, set at 0°		
9120123	· 3 UK 3.15A individually fused, child-proof, black, set at 45°		
6-way: 1 x custom module + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.008	· 5 socket outlets with earthing contact, child-proof, black, set at 35°		
912.014	· 5 French / UTE socket outlets, child-proof, black, set at 35°		
912.021*	· 4 UK 3.15A individually fused, child-proof, black, set at 90°		
9120122	· 4 UK 3.15A individually fused, child-proof, black, set at 45°		
6-way: 3 x custom modules + power socket outlet, black and red		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)			
912.024	· 1 socket outlet with earthing contact, child-proof, black, set at 35°		
	· 2 socket outlets with earthing contact, child-proof, red, set at 35°		
6-way: 2 x custom modules + power socket outlet, black and red		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)			
912.025	· 2 socket outlets with earthing contact, black, set at 35°		
	· 2 socket outlets with earthing contact, red, set at 35°		
6-way: 6 x custom modules		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; without power connection			
912.001	without socket outlets		
6-way: 1 x USB double charger (5.2V/2.15A) + custom modules + power socket outlets		Length: approx. 356 mm	CUSTOM USB CHARGER
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.0168	· 2 socket outlets with earthing contact, child-proof, black, set at 35°		
	· 1 x USB double charger, 3 x custom modules		
912.0169	· 3 Swiss / CH socket outlets, child-proof, black, set at 0°		
	· 1 x USB double charger, 3 x custom modules		
912.0172	· 2 French / UTE socket outlets, child-proof, black, set at 35°		
	· 1 x USB double charger, 3 x custom modules		
912.0170	· 2 UK 3.15A individually fused, child-proof, black, set at 90°		
	· 1 x USB double charger, 2 x custom modules		

Art. no. | Version