

CP M SNT3 1000W 24V 40A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16


D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



PRO-M = Power-Reliable-Optimized

The perfectly reliable power supply for automation technology.

The ten different versions for the 24V-DC power supply all feature a solid but thin metal housing which enables them to be installed without any side gaps. This results in less space required on the mounting rail. Wide range of AC/DC inputs and a wide temperature range enable them to be used anywhere. Because of its high efficiency, resistance to overloads and high power reserves, the PRO-M is a trusted power supply for use in any application. The three-phase PRO-M power supply modules continue to function reliably when one phase fails (i.e., in two-phase mode).

General ordering data

Order No.	8951420000
Type	CP M SNT3 1000W 24V 40A
Version	Power supply, switch-mode power supply unit
GTIN (EAN)	4032248742646
Qty.	1 pc(s).

CP M SNT3 1000W 24V 40A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Length	150 mm	Width	180 mm
Height	130 mm	Depth	150 mm
Weight	4 kg	Net weight	4,230 g

Temperatures

Operating temperature	-25 °C...+70 °C	Storage temperature	-40 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

Input

AC current consumption	2.0 A @ 3 x 500 V AC / 2.5 A @ 3 x 400 V AC	Conductor connection system	Screw connection
DC current consumption	1.3 A @ 800 V DC / 2.4 A @ 450 V DC	DC input voltage range	450...800 V DC (max. 500 V DC acc. to UL508)
Frequency range AC	47...63 Hz	Input fuse	No
Input fuse (internal)	No	Input voltage range AC	3 x 320...3 x 575 V AC / 2 x 360...2 x 575 V AC
Recommended back-up fuse	6 A / DI, safety fuse 10 A, Char. B, circuit breaker 6...8 A, Char. C, circuit breaker	making current	max. 60 A
rated input voltage	3 x 400...3 x 500 V AC (wide-range input)		

output

Conductor connection system	Screw connection	Output current	40 A
Output power	960 W	Output voltage type	DC
Output voltage, max.	29.5 V	Output voltage, min.	22.5 V
Output voltage, note	(adjustable via potentiometer on front)	Overload protection	Yes
Parallel connection option	yes, max. 3	Powerboost @ 24 V DC, 60 °C	48 A for 1 min, ED = 5 %
Rated (nominal) output current @ U _{Nom}	40 A @ 60 °C	continuous output current @ 24 V DC	48 A @ 45 °C, 42.7 A @ 55 °C, 30 A @ 70 °C
rated output voltage	24 V DC ± 1 %	residual ripple, breaking spikes	< 50 mV _{SS} @ 24 V DC, I _N

General data

AC failure bridging time @ I _{Nom}	> 25 ms at 3 x 500 V AC / > 20 ms at 3 x 400 V AC	Current limiting	> 120 % I _N
Degree of efficiency	91 % @ 3 x 500 V AC / 91 % @ 3 x 400 V AC	Housing version	Metal, corrosion resistant
Indication	Operation, green LED	MTBF	> 500,000 h acc. to IEC 1709 (SN29500)
Mounting position, installation notice	Horizontal on TS35 mounting rail, with 50 mm of clearance at top and bottom for air circulation. Can be mounted side by side with no space in between.	Operating temperature	-25 °C...+70 °C
Power factor (approx.)	> 0.6 @ 3 x 500 V AC / > 0.6 @ 3 x 400 V AC	Protection against over-heating	Yes
Protection against reverse voltages from the load	30...35 V DC	Short-circuit protection	Yes
Weight	4 kg		

Creation date November 19, 2012 2:27:36 PM CET

Catalogue status 06.11.2012 / We reserve the right to make technical changes.

2

CP M SNT3 1000W 24V 40A
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data
EMC / shock / vibration

Limiting of mains voltage harmonic currents	in accordance with EN 61000-3-2	Noise emission acc. to EN55022	Class B
Interference immunity test acc. to	EN 61000-4-2 (ESD) EN 61000-4-3 and EN 61000-4-8 (fields) EN 61000-4-4 (burst) EN 61000-4-5 (surge) EN 61000-4-6 (conducted) EN 61000-4-11 (dips)	Shock resistance IEC 60068-2-27	30 g in all directions

Insulation coordination

Class of protection	I, with PE connection	Insulation voltage	3 kV input/output; 2 kV input/earth; 0.5 kV output/earth
Pollution severity	2	electrical isolation, input-earth	2 kV
electrical isolation, input-output	3 kV	electrical isolation, output-earth	0.5 kV

Electrical safety (applied standards)

Electrical machine equipment	Acc. to EN60204	For use with electronic equipment	Acc. to EN50178 / VDE0160
Protection against dangerous shock currents	Acc. to VDE0106-101	Protective separation / protection against electrical shock	VDE0100-410 / acc. to DIN57100-410
Safety extra-low voltage	SELV acc. to EN60950, PLEV acc. to EN60204	Safety transformers for switch-mode power supplies	Acc. to EN 61558-2-17

Connection data (input)

Conductor cross-section, AWG/kcmil , max.	10	Conductor cross-section, AWG/kcmil , min.	26
Conductor cross-section, flexible , min.	0.5 mm ²	Conductor cross-section, rigid , max.	6 mm ²
Conductor cross-section, rigid , min.	0.5 mm ²	Number of terminals [Input]	4 for L1/L2/L3/PE
Tightening torque, max.	0.6 Nm	Tightening torque, min.	0.5 Nm
Wire connection cross section, flexible (input), max.	2.5 mm ²		

Connection data (output)

Conductor cross-section, AWG/kcmil , max.	6	Conductor cross-section, AWG/kcmil , min.	22
Conductor cross-section, flexible , max.	10 mm ²	Conductor cross-section, flexible , min.	0.5 mm ²
Conductor cross-section, rigid , max.	16 mm ²	Conductor cross-section, rigid , min.	0.5 mm ²
Number of terminals [Output]	5 (++) / (-)	Tightening torque, max.	0.6 Nm
Tightening torque, min.	0.5 Nm		

CP M SNT3 1000W 24V 40A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Approvals**

Institute (GERMLLOYD)



Certificate No. (GERMLLOYD)

94767-10

Institute (cULus)



Certificate no. (cULus)

E258476VOL1SEC30

Institute (cURus)



Certificate No. (cURus)

E25565 1VOLX3A19

Classifications

ETIM 3.0

EC001039

eClass 5.1

27-04-90-02

eClass 6.0

27-04-90-04

eClass 7.0

27-04-90-04

Approvals

Approvals

**Downloads**

Package insert

[Operating instructions](#)

Declaration of Conformity

[K469_12_11.pdf](#)

PDF


[Warranty information](#)

EPLAN

[8951420000.ema](#)[3-D model](#)

CP M SNT3 1000W 24V 40A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Electric symbol**

With DC connection, note polarity
Two-phase operation also possible