



8310

# LFM 101

The versatility and robust construction of the LFM is acknowledged around the world for a wide variety of users. It combines high specifications with functional design, resulting in a long product life.



While primary intended for industrial uses, the LFM adapts equally well for domestic use. The magnifying head is made of ABS polymer, combining lightness with high impact strength. The 22 Watt energy saving circular fluorescent lamp provides a high light-output with a minimum of heat. The  $\varnothing 127$  mm glass lens is positioned in the middle of the circular tube, the ideal way of illuminating an object, virtually eliminating shadows. A hinged lens cover is standard; it acts like a dust cover and prevents the lens from acting like a burning-glass. It is removable when not required. A transparent tube protection cover, made from rigid polycarbonate is standard. For additional magnification, secondary lenses can be fixed to LFM in seconds.

## RELATED PRODUCTS

AH-table clamp  
8990  
Task light accessories



CC surface mounted bracket  
8990  
Task light accessories



TE table bushing  
8990  
Task light accessories

Trolley  
8990  
Task light accessories

## 8310 LFM 101

## OPTIONS

## LFM 101

Article no.	Socket	Ilcos	Watt	Weight	Arm length	Lumen	IP	Colour rendering	Colours
8310-122-3	G10q	FC-E	1x22	3.4	1040	1350	20	80	<input type="checkbox"/>
8310-122-3G	G10q	FC-E	1x22	3.4	1040	1350	20	80	<input checked="" type="checkbox"/>

## LENS DATA

Option	Diopter primary	Diopter secondary	Total Magnification	Total Magnification %	Focal length (mm)	Lux	Lens size primary (mm)	Lens size secondary (mm)	Lens Size swing away
8310-122-3	3.00	0.00	1.8	175	333.3	1720	125	0	0
8310-122-3	3.00	4.00	2.8	275	142.9	7500	125	95	95
8310-122-3	3.00	8.00	3.8	375	90.9	8670	125	74	74

## ACCESSORIES

CC-bracket white	8990-507-1
BSP Bracket w/o. locking square	8990-045-1
BSP Wall bracket w looking square	8990-023-1
Attachment lins no 1(4 diopter) MO24	8900-093
Attachment lins no 2(8 diopter) MO25	8900-094

## DESIGNATION

