





Product Sheet

Part Number: CQM 04/2




Family	inserts
Version	crimp connections
Series	CQ
Product type	for male contacts 40A and 10A
Model	male insert
Reference standard	EN 61984 (2001-11)
No. of poles	4 poles + 
Auxiliaries poles	2 poles (10A max - 250V/4kV/3)
Voltage (V)	400V/690V
Current (A)	40A (A.C./D.C.)
Quality mark	  
IP degree of protection	degree of protection IP20 without enclosure, IP66/67 and IP69K with enclosure (EN 60529)
Fixing centre distance	size "32.13"
Impulse withstand voltage	6kV

The information and the dimensions contained are not binding and may be changed without prior notice.
The drawing's dimensions are in mm.

Pollution degree

3

Notes



CQ 04/2 inserts:

- enclosures: size 32.13:
 - CQ insulating type
 - CQS EMC
- rated voltage according to UL/CSA: 600V- insulation resistance: >10 GOhm
- ambient temperature limit: -40°C ... +125°C
- are made of self-extinguishing thermoplastic resin UL 94 V0
- mechanical life: < 0.3 mOhm (4 poles)
 - <>< 3 mOhm (2 poles)

The information and the dimensions contained are not binding and may be changed without prior notice.
The drawing's dimensions are in mm.