




## Product Sheet


**Part Number:** CXF 6/6



<b>Family</b>	CLASS insert series
<b>Version</b>	crimp connections
<b>Series</b>	CX
<b>Product type</b>	for female contacts 100A and 16A
<b>Model</b>	female insert
<b>Reference standard</b>	EN 61984 (2001-11)
<b>No. of poles</b>	6 poles + 
<b>Auxiliaries poles</b>	6 poles (16A max - 400V)
<b>Voltage (V)</b>	690V
<b>Current (A)</b>	100A (A.C./D.C.)
<b>Quality mark</b>	 US 600V  GOST
<b>IP degree of protection</b>	IP20 degree of protection without enclosure; IP65, IP66, IP67, IP68 (EN 60529) and IP69K (DIN 40050 - 9) with enclosure
<b>Fixing centre distance</b>	size "104.27"
<b>Impulse withstand voltage</b>	8kV
<b>Pollution degree</b>	3

The information and the dimensions contained are not binding and may be changed without prior notice.  
The drawing's dimensions are in mm.

Notes



CXF/M 6/6

- characteristics according to EN 61984:
  - 100A 690V 8kV 3
  - 16A 400V 6kV 3
- insulation resistance: > 10 GOhm
- ambient temperature limit: -40 °C ... +125 °C
- made of self-extinguishing thermoplastic resin UL 94 V0
- mechanical life: > 500 cycles
- contact resistance: < 0,3 mOhm (100A) - < 1 mOhm (16A)
- for contact crimping, see the crimp tool section (100A contacts CG series, and 16A contacts CC series)
- enclosures: size "104.27":
  - C-TYPE IP65/IP66
  - C7 IP67 stainless steel lever
  - V-TYPE IP65/IP66 stainless steel lever
  - T-TYPE IP65 insulating
  - JEI zinc-plated steel lever
  - BIG hoods
  - W-Type for aggressive environment
  - EMC
  - central lever
  - IP68
- panel supports: COB
- enclosures: bulkhead mounting housings, high construction housings or high construction hoods

The information and the dimensions contained are not binding and may be changed without prior notice.  
The drawing's dimensions are in mm.