

Data Sheet Fujitsu Display B22T-7 LED proGREEN Displays

Advanced display: 54.6 cm (21.5-inch) widescreen Best ergonomic and energy saving solutions for office applications

The Fujitsu Display B22T-7 LED proGREEN offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with HDMI, DVI and Analog

Representative design with space saving front frame and smart details like discretely integrated speakers















Technical details

Special features	
special leadures	4-in-1 Stand, Eco button for Eco mode and 3-coloured Eco status LED, Pivot, DisplayView™ IT Suite, 24/7 usage
Ergonomic stand	
Stand	4-in-1 Stand
Height adjust range	130 mm
Picture height over desk (min)	50 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	340°
Picture performance	
Panel and backlit	TN/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1000:1
Contrast - advanced	20,000,000:1
Response time typical	5 ms
Viewing angle (h/v) - typical	176°/170° CR5:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2
Size and resolution	LUC CUITILE
Aspect ratio	16:9
Diagonal Size	54.6 cm (21.5-inch)
Resolution (native)	
	1920 x 1080 pixel (recommended)
Resolution (interpolated)	1680 x 1050 pixel, 1440 x 900 pixel, 1366 x 768 pixel, 1280 x 1024 pixel, 1280 x 720 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
 Video modes	1080i/p, 720i/p, 576i/p, 480i/p
Picture size	476 x 268 mm
Pixel Pitch	0.248 mm
	U.240 IIIII
Frequencies	20. 02 111-
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Connectivity	1 110441
HDMI	1 x HDMI
DVI	1 x DVI (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 1.5 W
USB downstream	4 x USB 2.0
USB upstream	1 x USB
Ease-of-use menu	
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Color	sRGB, 6500K, 7500K, 9300K, Native, Custom Color (R,G,B)
lmage adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume
Information	Model name, S/N, Resolution/mode, Signal input
Setup	Input select, Language, DDC-CI, OSD-Timeout, Factory recall
Power consumption (typical, w/o sou	nd)
Soft switch off	0.2 W

Topicating with PR settings 18 W	Power save mode	0.3 W
Operating maximum brightness 2.2 W Power notes without sound, without USB Electrical values Electrical values Rated violage range 100 V - 240 V Power control 00 H - 260 ME Protection das 1 Compliance Cerebration according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT Eco Declaration, Nordic Swan Model Business 0051 USACGAnada FCC Class R, UI Australia/Neva Zealand CTck China CC Casul Arabia SSO Cidioal CC Conjuliance Info http://globalspia.cs/lipisa.com/bites/ectrificates Outling and Reliability 700000 h Dimensions Weight / Environmental Williams (Mix A) (M		
Power policy Supply display (Power notes) integrated reques (Power notes) without sound, without USB Electrical values Facted frequency 50 bit 2 bit 2 Rated frequency 50 bit 2 bit 2 Potection dass Compliance Furger C'entification according to EC Directive 2004/108/EFC, FN 60950, Rolfs, WEFF, IF-Eco-Declaration, Nordic Swan Model 82277 Germany TOW CS Russia GOST CKC Gass R, cUL Australia/New Zealand CKC Class R, cUL CKC Augustia South Konea K K A regentina 100-5 State Augustia CKC South Konea K K Augustia China CCC Sassard Avabia CKC South Acade 100-5 State Control CR China CCC Sassard Avabia CKC Chana CCC Sassard Avabia CKC Research Seal Control Ompliance link Duck Designation of Control CKC Research Seal Control CKC Research Seal Control Dilimensions Vibba Land (W x D x H) 51 fix x 20x 3 1 x 2 d x 1 x 5 fi		
Power notes		
Electrical values Clated voltage range 100 V - 240 V Rated frequency range 50 Hz. 60 Hz. Protection dass 1 Compliance Feature of the certification according to EC Directive 2004/108/EEC, EN 60950, RoMS, WEEE, IT Eco Declaration, Nordic Swan Model Model 6221-7 Germany Tilly GS Russia COST Russia COST USWA Canada CFC Class B, cUL Australia/New Zealand CHC Agentina CW S Taiwan GSM China CC South Korea KC South Korea KC Casadi Arabia GSM China CC South Jana Canada CTC South Korea KE Classian Si Fujisus com/sise/seet/lifeates Outlity and Reliability Total Signal Si Fujisus com/sise/seet/lifeates Dilmensions Virbout Stand (W x D x H) Si S x Si x 320 mm Dilmensions Virbout Stand (W x D x H) Si S x Si x 320 mm Dilmension with stand (W x D x H) Si S x Si x 320 mm Weig		,
Rated voltage range 50 Hz - 260 Vz Rated fequency range 50 Hz - 260 Hz Protection class 1 Compliance Europe 6 Centification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IF-Eco-Declaration, Nordic Swan Model 622 F7 Germany 70 VG USACTACIDAD FCC Class B, cUL USACTACIDAD FCC Class B, cUL USACTACIDAD CTC South Korea KC Variagentina 10V S Taiwan BSMI China CC South Korea KC China CC Sadid Arabia KSD China CC South Korea KC Will BE (demonstrate) Mptc yolkays E, DENEROY SIAR® 6.0. PERAI® Gold (dedicated regions), IS09241-307 (Pixel fault class I) Ombilate link http://goldaysis.tolysis.com/sistes/ertilicates Dimension without stand (W x D x H) 516 x 61 x 320 mm Birrection without stand (W x D x H) 516 x 61 x 320 mm Dimension with stand (W x D x H) 518 x 73 x 13 35 inh <th< th=""><th></th><th>without sound, without oob</th></th<>		without sound, without oob
Rate frequency range 50 Hz - 50 Hz Protection class 1 Complance Europe CF certification according to FC Directive 2004/188/FFC, FN 60950, RoHS, WFFF, IT Fco Declaration, Nordic Swan Model 80 277-7 Germany TÜV 65 Russia 6057 Russia OST Russia 10 Wc 12 W		100 V - 240 V
Protection class 1 Complance Europe CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IF-Eco-Declaration, Nordic Swan Model 8221-7 Germany TÜV 65 Russia COST USAC Gandad FCC Class B, CUL CURSIA Japan VCCI COST South Korea KC CA Argentina IÜV-5 CILIA CLASS ACCIDINATION CONTROL CONTR		
Compliance Europe CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration, Nordic Swan Model Model 877.7 Germany TUV GS Russia GLOSI USA/Canada PCC Class B, CUL Australia/New Zealand CTC Ck Japan VCQ South Korea KC Argentina TUV-S Talwan BSMI China CC South Arabia SASD Global COD Bisplays 6.0, ENERGY STAR** 6.0, EPEAT** Gold [dedicated regions], IS09241-307 (Pixel fault class I) Compliance link http://globalp.is.hijtsu.com/sites/certificates Compliance link 7000 h Dimensions Vellaght Fundromental 70000 h Dimensions Vellaght Fundromental 70000 h Dimensions Vellaght Fundromental 70000 h Dimension vith stand (Wx Dx H) 516 x 202 mm Distingation with stand (Wx Dx H) 516 x 202 mm Politocal Compliance 7.0 kg Weight (packed) 7.0 kg Signal 7.2 kg <	. , ,	
Every Book Ex certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Deciration, Nordic Swan Model Germany 10V G Russia 6CC flass B, CUL Australia/New Zealand FCC Class B, CUL Augentina 10V-5 Talwan 85M China CCC Saudi Avabia ASSO Global http://globalps.is. fujitsu.com/sites/certificates Compliance link http://globalps.is. fujitsu.com/sites/certificates Compliance link http://globalps.is. fujitsu.com/sites/certificates Willer (Harm Strade) 7000 h Dimension without stand (Wx Dx N) 516 x 320 mm Meight (packed) 20.31 x 240 x 12 60 inch Dimension with stand (Wx Dx N) 516 x 200 x 339 mm Quality X (V) = 1, 34 lbs Weight (packed) 7.0 kg Vielph (packed) 7.0 kg Vielph (packed) 8.3 lb Quality X (V) = 1, 12 lbs 1.2 y lbs Weight (mancked) 8.5 lb Weight (mancked) 8.5 lb Vielph (packed) 9.2 3 Tc (41 - 95 °F)		
Model B2ZF7 Germany TVV GS Rusila COST USA/Ganda ECC (Class B, CU) Australla/New Zealand CTick Japan VCC South Korea K Argentina 10½ S Taiwan BSMI China CCC Saudh Arabia SASO Global TCD Displays 6.0, ENERGY STAR® 6.0, EPEAI® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link TCD Displays 6.0, ENERGY STAR® 6.0, EPEAI® Gold (dedicated regions), ISO9241-307 (Pixel fault class II) Compliance link 100 Displays 6.0, ENERGY STAR® 6.0, EPEAI® Gold (dedicated regions), ISO9241-307 (Pixel fault class II) Compliance link 100 Displays 6.0, ENERGY STAR® 6.0, EPEAI® Gold (dedicated regions), ISO9241-307 (Pixel fault class II) Missellance III 700 Displays 6.0, ENERGY STAR® 6.0, EPEAI® Gold (dedicated regions), ISO9241-307 (Pixel fault class II) Dimension withouts stand (W x D x H) 516 x 61 x 320 mm Dimension withouts stand (W x D x H) 516 x 61 x 320 mm Dimension without stand (W x D x H) 516 x 61 x 320 mm Weight (packed) 7.0 kg Weight (pac	•	CE cortification according to EC Directive 2007/108/EEC EN 60050 PoHS WEEE IT Eco Declaration Mordic Swan
Germany TÜV GS Russia OOT LSWCanada FCC Class B, UU Australia/New Zealand CTC Ick South Korea KC A gentina TUV-S Taiwan BSMI China CCC Saudi Arabia CNO Global TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link http://globalsp.ts.fujitsu.com/sites/retrificates Ouality and Reliability TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Dimensions / Weight / Environmental 70000 h Dimensions / Weight / Environmental 70000 h Dimension without stand (W x D x H) 515 x 61 x 320 mm Poil x 2, 20 x 1 x 2, 30 x 1 x 2, 30 x 1 x 3.9 x 1 x 3.35 inch Weight (unacked) 9.8 kg Weight (unacked) 9.8 kg Weight (Monitor only) 3.1 kg 6.83 ibs 6.83 ibs Operating ambient temperature 2.5 3° C (41 - 95° T) Miscellaneous VEX. DOUT CI, Flat Display Mounting Interface VESA MIS-D 100 C. Kensington lock prepared </th <th></th> <th></th>		
Russia COST USA/Canda CCC Class B, UL Australia/New Zealand CTIC South Korea KC Taiwan BSWI China CC Saudi Arabia SSWI China CC Saudi Arabia SSWI Chompliance link USA psipps 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Miscellance link TOD Displays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Use (Salah Subara Link) TOD Splays 6.0, ENERGY STAR™ 6.0, EPEA™ Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Weight (unacked) Silk 6.5 1 x 3.30 mm College Coll		
USACanada FCC Class B, cUL Australa/New Zealand C-Fick Japan VCC South Korea KC Argentina TID VS Taiwan BSM I China CCC Saudi Arabia XSO Global TO Displays 6.0 ENERGY STAR® 6.0 EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel Fault class I) Compliance link http://globalsp.ss.fujitsu.com/sites/certificates Wall TO Displays 6.0 ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel Fault class II) MBF (demonstrated) 700000 h Williams of Wileylat / Environmental FERROR (MERCANDA) Dimension Without stand (W x D x H) 5165 x 12 x 30 mm Bis (S 1) x 30 mm 2031 x 7 87 x 13.35 inch Weight (packed) 7.0 kg 15 x 31 lbs Weight (unpacked) 8.0 kg 26 x 15 x 12 y 15 bs Weight (Monitor only) 3.1 kg 47 yeight (Monitor only) 3.1 kg 48 yeight (Monitor only) 4.5 x 12 x 15 x 15 x 15 x 15 x 15 x 15 x 1	•	
Australia/New Zealand C-Tick Japan VCC South Korea KC Argentina TÜV-S Taiwan BSMI China CC Saudi Arabia SSO Global TOD bisplays 6.0, FNERGY STAR® 6.0, FPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link http://globalsp.ts.fujuts.com/sites/certificates Builty and Reliability 70000 h Umensions Without stand (Wx Dx H) 516 x 61 x 320 mm Dimensions Without stand (Wx Dx H) 516 x 61 x 320 mm Dimensions with stand (Wx Dx H) 516 x 61 x 320 mm Weight (packed) 7,0 kg 15,4 3 lbs Weight (unpacked) 3.6 kg Weight (unpacked) 3.8 kg Weight (Monitor only) 3.1 kg Weight (Monitor only) 3.1 kg Wiscellaneous VEX.DOC (I, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Poskarding ambient temperature x 5x C (41 - 95°F) Bisplay delivered accessories onto DI-PD Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, AUSB cable 1.8 m (USB-A to USB-B), Power cabl		
Japan VCCI South Korea KC Argentina TUV S Taiwan BSMI China CCC Saudi Arabia XSO Global ICD Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link http://globalsp.ts/lujitsu.com/sites/certificates Walley TO000 h Dimensions Weight / Environmental 70000 h Dimensions Without stand (W x D x M) 516 x 60 x 320 mm Quality and (W x D x M) 516 x 200 x 339 mm Weight (packed) 7.0 kg Weight (packed) 7.0 kg Weight (unpacked) 7.0 kg As kg 8.0 kg Weight (Monitor only) 3.1 kg Bogeating ambient temperature 6.33 lbs Poperating ambient temperature 5.35 °C (41 - 95 °F) Miscellaneous Will Dubat cable 1.8 m, D SUB Data cable 1.8 m, VSB cable 1.8 m (USB A to USB A) power cable for wall socket (Euro Schuko Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories 20 kg 23 kl Kl 453 V 160 LB. with UK power cable, mandatory for Arabian countries </th <th></th> <th>·</th>		·
South Korea KC Argentina 10V-5 Tailwan BSM China CCC Saud Arabia ASAO Global TOD Displays 6.0, ENERGY STAR* 6.0, EPEAT* Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link http://globalsp.ts.fujitsu.com/sites/certificates Quality and Reliability 70000 h MTBF (demonstrated) 700000 h Dimensions / Weight / Environmental 516 x 61 x 320 mm Dimension without stand (W x D x H) 516 x 200 x 339 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm Use play (unpacked) 7.0 kg Weight (unpacked) 7.0 kg Weight (unpacked) 5.8 kg Weight (Monitor only) 3.1 kg Also 3.1 kg Miscellaneous VESA DDC (T, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content VIPO Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EET) 1.8 m, Quickstar flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories note Data cable s and audio cable detachable		
Agentina TÖV-S Taiwan 85MI Ckina CC Saudi Arabia ASO Global TOD Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), 1509241-307 (Pixel fault class II) Compliance link http://globalsp.ts.fujitsu.com/sites/cettificates Coultity and Reliability TO000 h MTBF (demonstrated) 70000 h Dimensions / Weight / Environmental* 70000 h Dimension without stand (W x D x H) 516 x 20 x 320 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 2.40 x 12.60 inch 15 x 31 ks Weight (packed) 7.0 kg 4 yill 15 x 31 ks Weight (unpacked) 5.8 kg 12.79 lbs Weight (Monitor only) 3.1 kg Applies 4.3 ks Miscellaneous VESA DDC (I, Flat Display Mounting Interface VESA MIS-D 100 C, Kersington lock prepared Package content 7.0 kg Display delivered accessories note 0VI-D Data cable 1.8 m, OSB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EET?) 1.8 m, Quickstart flyer, Utility CD, Warranny bookl	•	
Taiwan BSMI China CCC Saudi Arabia CSO Global TCO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link http://globalsp.ts.fujitsu.com/sites/certificates Ouality TOOD Intersions of Weight / Environmental Dimensions / Weight / Environmental 516 x 61 x 320 mm Dimension without stand (W x D x H) 516 x 200 x 339 mm Ediple (packed) 516 x 200 x 339 mm Weight (packed) 5.8 kg Ueight (unpacked) 5.8 kg Elizability Miscellance Weight (Monitor only) 5.9 S x (1-95 °F) Miscellaneous VEXADOCY C, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Pockage content Div1D pata cable 1.8 m, D SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EET?) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Order Information BUKL'1453V160-UK- with UK power cable, and dEL, mandatory for Arabian countries Order Code BUKL'1453V160-UK- with UK power cable, and dEL, mandatory for Indonesia BUKL'1453V160-UNT - With China power cable, and dEL, mandatory for Indonesia <t< th=""><th></th><th></th></t<>		
China CCC Saud Rabia SASO Global CX Displays 6.0, ENERGY STAR® 6.0, EPEAI® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link thttp://globalsp.ts.lujisu.com/sites/certificates Quality and Reliability Tomos 1 MTBF (demonstrated) 70000 h Dimensions / Weight / Environment 1 Dimensions / Weight / Environment 516 x 61 x 320 mm Dimension with stand (W x D x H) 516 x 61 x 320 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm Qual x x.8 x x 13.35 inch 20.31 x 2.40 x 12.60 inch Weight (packed) 7.0 kg Weight (unpacked) 5.8 kg Early Is 5.8 kg Gespit (Monitor only) 3.1 kg Bogerating ambient temperature 5.95 *C(1 - 95 *F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Will Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-A)		
Saduil Arabia SASO Global TOD Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance lisk http://globalsp.st. fujitsu.com/sites/certificates Coulity and Reliability ***********************************		
Global 1CO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I) Compliance link http://globalsp.ts.fujitsu.com/sites/certificates Walfier (demonstrated) 70000 h Dimensions / Weight / Environmentat Dimension without stand (W x D x H) 516 x 61 x 320 mm 20.31 x 2.40 x 12.60 inch Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 7.87 x 13.35 inch Weight (packed) 7.0 kg 15.43 lbs Weight (unpacked) 15.43 lbs Weight (unpacked) 5.3 kg 12.79 lbs Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature 6.35 °C (41 - 95 °F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Order Code 526361-K1453-V160 EAN Code 40051554497729 Warranty Warranty EAN Code 40051554497729 Warranty EAN Code 40051554497729 Warranty Warranty ### Code 1505154497729 ### Code 1505154497729 ### Code 40051554497729 ### Code 4005154745497160 ### Code 40051554497729 ### Code 4005154745497160 ### Code 40051554497729 ### Code 4005154745497160 ### Code 4005154745497160 ### Code 40051554497729 ### Code 4005154745497160 ### Code 4005154745497		
Compliance link http://globalsp.ts.fujitsu.com/sites/certificates Quality and Reliability MTBF (demonstrated) 70000 h Dimensions / Weight / Environmental Dimension without stand (W x D x H) 516 x 61 x 320 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 2.40 x 13.60 inch Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 7.87 x 13.35 inch Weight (packed) 7.0 kg 15.43 lbs Weight (unpacked) 5.8 kg 12.79 lbs Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature 5 - 35 °C (41 - 95 °F) Miscellaneous Miscellaneous VESA DDO/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content DIV-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EET) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Drigory delivered accessories notes Data cables and audio cable detachable on display Order Information Order Gode S26361-K1453-V160 Audio cable and CEL, mandatory for Arabian countries BDL:K1453V160-URN - with Uki power cable, mandatory for Indonesia BDL:K1453V160-URN - with Uki power cable, mandator		
Quality and Reliability 70000 h Dimensions / Weight / Environmental 70000 h Dimension without stand (W x D x H) 516 x 61 x 320 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 2 x 7 x 13.35 inch 20.31 x 2 x 32 x 13.35 inch Weight (packed) 7.0 kg 15 x 3 ibs 12.79 lbs Weight (Monitor only) 3.1 kg 6 x 83 lbs 6.83 lbs Operating ambient temperature 5 - 35 °C (41 - 95 °F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EET) 1.8 m, Duickstart flyer, Uillity CD, Warranty booklet, Safety booklet Order information Order information Order forforde \$ 26361-K1453-V160 Country specific order code BUL-K1453 V160-UK - with UK power cable, mandatory for Arabian countries BUL-K1453 V160-UH - with Uhi port label, mandatory for Indonesia BUL-K1453 V160-UH - with Uhi port label, mandatory for Indonesia BUL-K1453 V160-UH - with Uhi port l		
MTBF (demonstrated) 70000 h Dimensions / Weight / Environmental 516 x 61 x 320 mm Dimension without stand (W x D x H) 516 x 200 x 339 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm Weight (packed) 7.0 kg Weight (unpacked) 5.8 kg Eight (Monitor only) 3.1 kg By Gerating ambient temperature 5.35 °C (41 - 95 °F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Outickstart flyer, Utility CD, Warranty booklet, Safety booklet Order Information Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UH - with China power cable and CEL, mandatory for China BDL:K1453V160-UH - with Import label, mandatory for Indonesia BDL:K1453V160-UH - with Import label, mandatory for Indonesia BDL:K1453V160-UH - with Import label, mandatory for countries where import with EU cable is not allowed EAN Code 4051554497729	•	nttp://giobaisp.ts.rujitsu.com/sites/certificates
Dimensions / Weight / Environmental Dimension without stand (W x D x H) 516 x 61 x 320 mm 20.31 x 2.40 x 12.60 inch Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 7.87 x 13.35 inch Weight (packed) 7.0 kg 15.43 lbs Weight (unpacked) 5.8 kg 12.79 lbs Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature 5 - 35 °C (41 - 95 °F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Order information Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UK - with UK power cable, mandatory for Indonesia BDL:K1453V160-UN - with Unport Label, mandatory for countries where import with EU cable is not allowed EAN Code Warranty Warranty		70000
Dimension without stand (W x D x H) 516 x 61 x 320 mm Dimension with stand (W x D x H) 516 x 200 x 339 mm Weight (packed) 7.0 kg Weight (unpacked) 5.8 kg Weight (Monitor only) 5.8 kg Operating ambient temperature 5.35° (41-95°F) Miscellaneous VESA DDC/CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EET) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Verder information Order Code Se361-K1453-V160 Country specific order code and EU:X1453V160-UK - with UK power cable, mandatory for Arabian countries BUE:X1453V160-UK - with UK power cable, mandatory for Indonesia BUE:X1453V160-UK - with UK power cable, mandatory for Indonesia BUE:X1453V160-UN - With Import label, mandatory for countries where import with EU cable is not allowed EAN Code 4051554497729		70000 n
Dimension with stand (W x D x H) 516 x 200 x 339 mm 20.31 x 7.87 x 13.35 inch		F16 (1 220
Dimension with stand (W x D x H) 516 x 200 x 339 mm Weight (packed) 7.0 kg 15.43 lbs Weight (unpacked) 15.49 lbs Weight (Monitor only) 3.1 kg Operating ambient temperature 5.35 °C (41 - 95 °F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content DIVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Drefer Code Country specific order code 8DL:K1453V160-UK- with UK power cable, mandatory for Arabian countries BDL:K1453V160-UH- with UK pina power cable and CEL, mandatory for China BDL:K1453V160-UH- with Import label, mandatory for Indonesia BDL:K1453V160-UH - with Import label, mandatory for Indonesia BDL:K1453V160-UH - with Import label, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:K1453V160-UH - with UK power cable, mandatory for Indonesia BDL:	Dimension without stand (W X D X H)	
Weight (packed) 7.0 kg 15.43 lbs Weight (unpacked) 5.8 kg 12.79 lbs Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature 5-35 °C (41-95 °F) Miscellaneous Wiscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Order information Order Code Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UH - with Uhina power cable, mandatory for China BDL:K1453V160-UH - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty	Discoursian with the day (W., D., II)	
Weight (packed) 7.0 kg Weight (unpacked) 5.8 kg Weight (Monitor only) 3.1 kg Weight (Monitor only) 5.35°C (41 - 95°F) Miscellaneous 5.35°C (41 - 95°F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information S26361-K1453-V160 Country specific order code SDL:K14533V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-ID - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-ID - with Import label, mandatory for countries where import with EU cable is not allowed EAN Code 4051554497729	Dimension with stand (W X D X H)	
Weight (unpacked) 5.8 kg 12.79 lbs Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature Miscellaneous Miscellaneous Wesh DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty	W-:-k-/11\	
Weight (unpacked) 5.8 kg Weight (Monitor only) 3.1 kg Operating ambient temperature 5-35°C (41-95°F) Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order information Order Code \$26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UH - with China power cable and CEL, mandatory for China BDL:K1453V160-U - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code 4051554497729 Warranty	weight (packed)	•
Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature 5 - 35 °C (41 - 95 °F) Miscellaneous Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-ID - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		
Weight (Monitor only) 3.1 kg 6.83 lbs Operating ambient temperature 5 - 35 °C (41 - 95 °F) Miscellaneous Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order Information Order Code Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty	weight (ипраскеd)	
6.83 lbs Operating ambient temperature 5 - 35 °C (41 - 95 °F) Miscellaneous Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type (EE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		
Miscellaneous Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty	weight (Monitor only)	
Miscellaneous Miscellaneous VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		
MiscellaneousVESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock preparedPackage contentDVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety bookletDisplay delivered accessories notesData cables and audio cable detachable on displayOrder informationOrder Code\$26361-K1453-V160Country specific order codeBDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowedEAN Code4051554497729Warranty		5 - 35 °C (41 - 95 °F)
Package content Display delivered accessories DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-INF - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		VICA DDC/ CLITI- Disala Manaka a labarfa a VICA MIC D 100 C V
DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		vesa אינטא איטיר כו, Flac visplay Mounting Interrace Vesa Mis-ע וטע כ, Kensington lock prepared
for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet Display delivered accessories notes Data cables and audio cable detachable on display Order information Order Code S26361-K1453-V160 Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		DV// DD-t
Order Code Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-UH - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet
Order Code Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty	. ,	Data cables and audio cable detachable on display
Country specific order code BDL:K1453V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		
BDL:K1453V160-CHN - with China power cable and CEL, mandatory for China BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code Warranty		
BDL:K1453V160-ID - with Import label, mandatory for Indonesia BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code 4051554497729 Warranty	Country specific order code	
BDL:K1453V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed EAN Code 4051554497729 Warranty		
EAN Code 4051554497729 Warranty		
Warranty	FAN Code	<u> </u>
		L21 IUFFUCIUUF
Standard Warranty 3 years (depending on country)	•	
	Standard Warranty	3 years (depending on country)

Warranty	
Service level	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu Display B22T-7 LED proGREEN, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B22T-7 LED proGREEN, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-11-28 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms Copyright © Fujitsu Technology Solutions