

ELEVATOR

The elevator is powered straight away

ELEVATOR fits perfectly in any working environment. At 79 mm in diameter, ELEVATOR is ideal for integrating power and data connections in tiny spaces. Simply press down with your finger to raise and lower ELEVATOR. Two versions of ELEVATOR are available: with three socket outlets or with one socket outlet and two data connections.

Installation is incredibly simple. ELEVATOR is placed in a cut-out 79 mm in diameter and secured to the desktop or tabletop from below using a lock ring.

The benefits at a glance

- \cdot Press down with your finger to raise
- · 2 configurations
- · Suitable for standard 79 mm hole
- · Quick and easy to install
- · Suitable for retrofitting
- \cdot Aluminium polished and brushed or matt chrome
- $\cdot \ {\rm Classic} \ {\rm design}$
- · For desktop or tabletop thicknesses of 16 60 mm

ELEVATOR

Art. no.	Version		
ELEVATOR	R power strip		-
	eel look profile, power input: 2.0 m H05VV-F 3G 1.5 mm² with end sleeves and ntact mounting plug (included)	18030	
928.002	· 2 x socket outlet with earthing contact, shuttered, black	_	
928.003	· 1 x socket outlet with earthing contact, shuttered, black	928.00	
	· 2 x Euro socket outlet, shuttered, black	920.00)2
928.007	· 2 x French / UTE socket outlet, shuttered, black	(6	
928.017	· 1 x socket outlet with earthing contact, shuttered, 1 x USB double charger (5.2 V/ 2.15A)	U NEU	
928.020	· 1 x French / UTE socket outlet, shuttered, 1 x USB double charger (5.2 V/ 2.15A)	U NEU	928.003
928.024	· 2 x Swiss / T23 socket outlets, shuttered, with mounting plug (included), black	+ NEU	920.003
	profile, matt chrome, power input: 0.5 m H05VV-F3G 1.5 mm² with GST18 plug; cables and plug and/or socket	1	
928.004	· 1 x socket outlet with earthing contact, shuttered, black, set at 35°	-	
	· 2 x CAT6 RJ45 with 3.0 m data cable and RJ45 plug		928.020
928.005	· 1 x socket outlet with earthing contact, shuttered, black, set at 35°		920.020
	· 1 x CAT6 RJ45 with 3.0 m data cable and RJ45 plug		
	· 1 x USB 3.0 A socket with 3.0 m data cable and USB 3.0 A plug		
928.006	· 1 x socket outlet with earthing contact, shuttered, black, set at 35°		
	· 1 x CAT6 RJ45 with 3.0 m data cable and plug		
	· 1 x HDMI socket with 3.0 m data cable and socket		
928.008	· 1 x French / UTE socket outlet, shuttered, black, set at 35°	- 11	100
	· 2 x CAT6 RJ45 with 3.0 m data cable and RJ45 plug		, a
928.009	· 1 x French / UTE socket outlet, shuttered, black, set at 35°	TII ,	928.004
	· 1 x CAT6 RJ45 with 3.0 m data cable and RJ45 plug	8	520.001
	· 1 x USB 3.0 A socket with 3.0 m data cable and USB 3.0 A plug	1	
928.010	· 1 x French / UTE socket outlet, shuttered, black, set at 35°		
	· 1 x CAT6 RJ45 with 3.0 m data cable and RJ45 plug		
	· 1 x HDMI socket with 3.0 m data cable and socket		000.005
928.026	· 1 x UK 5 A individually fused, shuttered, black, set at 90°	U NEU	928.005
	· 1 x USB double charger (5.2 V/ 2.15A)		

Accessories

Version Art. no.

Hole saw dia	Hole saw diameter 79 mm for installing the ELEVATOR		
928.900	· In wood/plastic; cutting depth up to 44 mm		
918.900	· Mounting tool for hole saw with centring drill		





Watch the ELEVATOR installation film at bachmann.com

