



## HEAT SHRINKABLE-FULLY NYLON FEMALE DISCONNECTORS "H"(SINGLE CRIMP TYPE)

**MAXIMUM ELECTRIC CURRENT:**

A.W.G.	22	20	18	16	14	12	10
AMP.	9	12	17	18	30	35	50

**MAXIMUM ELECTRICAL RATING:** 300 VOLTS MAX.

**INSULATION MATERIAL:** NYLON & HIGH DENSITY PE.

**INSULATION COLOR:**

22-16A.W.G.: RED ■ 16-14A.W.G.: BLUE ■

12-10A.W.G.: YELLOW ■

**TERMINAL MATERIAL:** BRASS

WIRE RANGE A.W.G. mm <sup>2</sup>	ITEM NO.	NEMA TAB	DIMENSION inch(mm)			INSULATED COLOR	Q'TY BOX
			W	D	L		
22-16 A.W.G. 0.5-1.5 mm <sup>2</sup>	FDfNYH1-250	.032X.250 0.8X6.35	0.26 6.6	0.256 6.500	1.437 36.5	RED	500
16-14 A.W.G. 1.5-2.5 mm <sup>2</sup>	FDfNYH2-250	.032X.250 0.8X6.35	0.26 6.6	0.256 6.500	1.437 36.5	BLUE	500
12-10 A.W.G. 4-6 mm <sup>2</sup>	FDfNYH5-250	.032X.250 0.8X6.35	0.26 6.6	0.295 7.500	1.457 37	YELLOW	500

