



## MG-Filter systems

for connection of extraction arms



| Article number                                   | Description  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
|--|--|-------------|------|------------|-----|------------|-----|-----------------------------------|----|------------------------------|-----|---------------------------------|---------|---------------|-----|--|-----|--|----------|---|----------|---|------------------|--------------------------------------|-----|-------------------------------|-----|-------------|---------|--------------------------------------|---|
| 100-1000-ESD                                     | <p>Filter unit MG100 with connection for one or two extraction arms<br/>(Connection hose is ordered separately)</p> <p><b>Technical data MG100</b></p> <table border="0"> <tr><td>Height (mm)</td><td>610</td></tr> <tr><td>Width (mm)</td><td>460</td></tr> <tr><td>Depth (mm)</td><td>210</td></tr> <tr><td>Weight incl filter cartridge (kg)</td><td>18</td></tr> <tr><td>Noise level dB(A) at 1 meter</td><td>52</td></tr> <tr><td>Voltage 1-phase 50/60Hz (Volt)</td><td>100-240</td></tr> <tr><td>Effect (Watt)</td><td>100</td></tr> <tr><td>Max. suction capacity (m<sup>3</sup>/hr)</td><td>100</td></tr> <tr><td>Micro filter HEPA-styled (separation degree DOP)</td><td>&gt;99,97 %</td></tr> <tr><td>Chemisorbant gas filter (separation degree)</td><td>&gt;95 %</td></tr> <tr><td>Filter alarm</td><td>Yes, light/sound</td></tr> <tr><td>Warranty, except for filters (years)</td><td>2</td></tr> </table>   | Height (mm) | 610  | Width (mm) | 460 | Depth (mm) | 210 | Weight incl filter cartridge (kg) | 18 | Noise level dB(A) at 1 meter | 52  | Voltage 1-phase 50/60Hz (Volt)  | 100-240 | Effect (Watt) | 100 | Max. suction capacity (m <sup>3</sup> /hr) | 100 | Micro filter HEPA-styled (separation degree DOP) | >99,97 % | Chemisorbant gas filter (separation degree) | >95 %    | Filter alarm                                | Yes, light/sound | Warranty, except for filters (years) | 2   |                               |     |             |         |                                      |   |
| Height (mm)                                      | 610  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Width (mm)                                       | 460  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Depth (mm)                                       | 210  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Weight incl filter cartridge (kg)                | 18   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Noise level dB(A) at 1 meter                     | 52   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Voltage 1-phase 50/60Hz (Volt)                   | 100-240  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Effect (Watt)                                    | 100  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Max. suction capacity (m <sup>3</sup> /hr)       | 100  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Micro filter HEPA-styled (separation degree DOP) | >99,97 %   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Chemisorbant gas filter (separation degree)      | >95 %  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Filter alarm                                     | Yes, light/sound   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Warranty, except for filters (years)             | 2  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-1032-ESD                                     | <p>Filter unit MG100 with flexible extraction arms Ø 32 mm<br/>2 pcs of extraction arms (3)OF15 are included in the delivery.</p>  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-1055-ESD                                     | <p>Filter Unit MG100 with flexible extraction arms Ø 55 mm<br/>2 pcs of extraction arms OF15 with ALFA nozzle are included in the delivery.</p>  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-2000-ESD                                     | <p><b>Replacement filters MG100</b></p> <p>Micro/gas filter, standard</p> <p>Micro/gas filter, MEK</p> <p>Micro/gas filter, glue</p> <p>Micro/gas filter, ammonia</p> <p>Micro/gas filter, CO<sub>2</sub></p>  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-2003-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-2005-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-2006-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 100-2007-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-1000-ESD                                     | <p>Filter system MG400 with integrated prefilter for connection to<br/>max eight 60 mm extraction arms or two CBC-A air curtain cabinets<br/>Remote control for variable speed, filter lifetime indication and<br/>alarm functions.<br/>(Connection hose is ordered separately)</p> <p><b>Technical data MG400</b></p> <table border="0"> <tr><td>Height (mm)</td><td>1016</td></tr> <tr><td>Width (mm)</td><td>796</td></tr> <tr><td>Depth (mm)</td><td>402</td></tr> <tr><td>Weight (kg)</td><td>68</td></tr> <tr><td>Noise level dB(A) at 1 meter</td><td>&lt;55</td></tr> <tr><td>Voltage 1-phase 50/60 Hz (Volt)</td><td>115-230</td></tr> <tr><td>Effect (Watt)</td><td>300</td></tr> <tr><td>Max. suction capacity (m<sup>3</sup>/h)</td><td>400</td></tr> <tr><td>Max vacuum, (Pa)</td><td>2300</td></tr> <tr><td>Micro filter (tested separation degree DOP)</td><td>&gt;99,97 %</td></tr> <tr><td>Chemisorbant gas filter (separation degree)</td><td>&gt;95 %</td></tr> <tr><td>Visual filter guard gas</td><td>Yes</td></tr> <tr><td>Visual filter guard particles</td><td>Yes</td></tr> <tr><td>Process air</td><td>0-50 °C</td></tr> <tr><td>Warranty, except for filters (years)</td><td>2</td></tr> </table> <p><b>Replacement filters MG400</b></p> <p>Micro/Gas filter, standard</p> <p>Micro/Gas filter, clean room</p> <p>Micro/Gas filter, MEK</p> <p>Micro/Gas filter, glue</p> <p>Micro/Gas filter, ammonia</p> <p>Micro/Gas filter, CO<sub>2</sub></p> | Height (mm) | 1016 | Width (mm) | 796 | Depth (mm) | 402 | Weight (kg)                       | 68 | Noise level dB(A) at 1 meter | <55 | Voltage 1-phase 50/60 Hz (Volt) | 115-230 | Effect (Watt) | 300 | Max. suction capacity (m <sup>3</sup> /h)  | 400 | Max vacuum, (Pa)                                 | 2300     | Micro filter (tested separation degree DOP) | >99,97 % | Chemisorbant gas filter (separation degree) | >95 %            | Visual filter guard gas              | Yes | Visual filter guard particles | Yes | Process air | 0-50 °C | Warranty, except for filters (years) | 2 |
| Height (mm)                                      | 1016   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Width (mm)                                       | 796  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Depth (mm)                                       | 402  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Weight (kg)                                      | 68   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Noise level dB(A) at 1 meter                     | <55  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Voltage 1-phase 50/60 Hz (Volt)                  | 115-230  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Effect (Watt)                                    | 300  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Max. suction capacity (m <sup>3</sup> /h)        | 400  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Max vacuum, (Pa)                                 | 2300   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Micro filter (tested separation degree DOP)      | >99,97 %   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Chemisorbant gas filter (separation degree)      | >95 %  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Visual filter guard gas                          | Yes  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Visual filter guard particles                    | Yes  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Process air                                      | 0-50 °C  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| Warranty, except for filters (years)             | 2  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-2000-ESD                                     | <p>Micro/Gas filter, standard</p> <p>Micro/Gas filter, clean room</p> <p>Micro/Gas filter, MEK</p> <p>Micro/Gas filter, glue</p> <p>Micro/Gas filter, ammonia</p> <p>Micro/Gas filter, CO<sub>2</sub></p>  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-2002-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-2003-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-2005-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-2006-ESD                                     |  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| 450-2007-ESD                                     | <p>450-4000</p> <p>Prefilter cassette, 2 pcs</p>   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| PC-UK  | Power cord model United Kingdom  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| PC-EU  | Power cord model Europe  |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| PC-US  | Power cord model USA   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |
| PC-AU  | Power cord model Australia   |             |      |            |     |            |     |                                   |    |                              |     |                                 |         |               |     |  |     |  |          |   |          |   |                  |                                      |     |                               |     |             |         |                                      |   |

Please state which power cord you require for the units: