



TAPE ON REEL TYPE NYLON-FULLY INSULATED DOUBLE CRIMP RECEPTACLE DISCONNECTORS

MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14
AMP.	3	4	7	10	15

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: NYLON

INSULATION COLOR:

22-16A.W.G.: RED ■ 16-14A.W.G.: BLUE ■

TERMINAL MATERIAL: BRASS

WIRE RANGE A.W.G. mm ²	ITEM NO.	DIMENSION inch(mm)						CRIMPING TOOL	Q'TY BOX
		W	F	L	E	D	T		
22-16 A.W.G. 0.5-1.5 mm ²	FRFNVD1-156-T	0.154 3.9	0.276 7	0.992 25.3	0.433 11	.157 4.0	0.016 0.4	K.S.MODEL KM-70T WITH DIE INDEX NO.: TPF011	1000
16-14 A.W.G. 1.5-2.5 mm ²	FRFNVD2-156-T	0.154 3.9	0.276 7	0.992 25.2	0.433 11	.197 5.0	0.016 0.4	K.S.MODEL KM-70T WITH DIE INDEX NO.: TPF012	1000
	FRFNVD2-195-T	0.193 4.9	0.276 7	1.063 27	0.433 11	.197 5.0	0.016 0.4		500

