








## Product Sheet

**Part Number:** JCNEM 10





<b>Family</b>	JEI insert series
<b>Version</b>	screw terminal connections
<b>Series</b>	JCNE - JNE
<b>Product type</b>	with male contacts
<b>Type</b>	with plate
<b>Model</b>	male insert
<b>Reference standard</b>	EN 61984 (2001-11)
<b>Contact type</b>	tinned
<b>No. of poles</b>	10 poles + 
<b>Voltage (V)</b>	500V
<b>Current (A)</b>	16A (A.C./D.C.)
<b>Wire section</b>	0,5mm <sup>2</sup> - 4mm <sup>2</sup>
<b>Awg size</b>	20 - 12
<b>Quality mark</b>	    

The information and the dimensions contained are not binding and may be changed without prior notice.  
The drawing's dimensions are in mm.

<b>IP degree of protection</b>	IP20 degree of protection without enclosure; IP65, IP66, IP67, IP68 (EN 60529) and IP69K (DIN 40050 - 9) with enclosure
<b>Fixing centre distance</b>	size "57.27"
<b>Impulse withstand voltage</b>	6kV
<b>Pollution degree</b>	3

**Notes**

- for non-prepared conductors
- inserts with plate for section conductors:  
0.5 ÷ 4 mm<sup>2</sup> - AWG 20 ÷ 12
- conductors stripping length: 7 mm
- terminal screw torque: 0.5 Nm

JCNEF/M 10 inserts

- characteristics according to EN 61984:  
16A 500V 6kV 3  
16A 400/690V 6kV 2
- rated voltage according to UL/CSA: 600V
- insulation resistance: > 10 GOhm
- ambient temperature limit: -40 °C ... +125 °C
- are made of self-extinguishing thermoplastic resin UL 94 V0
- mechanical life: > 200 cycles
- contact resistance: < 1 mOhm
- enclosures: size "57.27":  
C-TYPE IP65/IP66  
C7 IP67 stainless steel lever  
V-TYPE IP65/IP66  
stainless steel lever  
T-TYPE IP65 insulating  
JEI zinc-plated steel lever  
BIG hoods  
W-TYPE aggressive environments  
EMC  
central lever  
IP68
- panel supports: COB

The information and the dimensions contained are not binding and may be changed without prior notice.  
The drawing's dimensions are in mm.



The information and the dimensions contained are not binding and may be changed without prior notice.  
The drawing's dimensions are in mm.