

PRODUCT SPECIFICATION

**Carl
Kammerling**
International

Brand	KASP
Product Range	Illuminated Combination Coil Cable Bike Lock
Catalogue number	750
Date	26/09/2008

Range Description

Illuminated Combination Coil Cable Bike Lock

Features

- High tensile multi-strand steel cable - Extra resistance to cut and pull attack methods
- Resettable 4 dial combination mechanism with key override - Unlock via the combination or key for added convenience
- Dial illumination system - Illuminates the combination dials for ease of use in low light conditions
- Versatile quick release mounting bracket - Allows lock to be fixed to the bike frame or seat post for easy transportation
- Supplied with 2 x dimple keys and a quick release mounting bracket.

This lock is supplied on a hanging backing card.



<p>Technical product information</p>	<p>Body – Die cast metal body, in a tough plastic casing.</p> <p>Cable – Vinyl coated, multi strand, twisted steel cable.</p> <p>Locking mechanism – Resettable, 4 dial combination locking mechanism. Key override featuring a pin tumbler cylinder with dimple key system. 5 pin cylinder featuring anti-pick mushroom top pins.</p> <p>To reset the lock to a combination of your choice:</p> <ol style="list-style-type: none"> 1) Using the correct combination code, open the lock by aligning the dial wheels with the indicators on the lock body (pre-set factory combination code 0-0-0-0) 2) Hold the lock either side of the combination barrel and pull apart until the lock shackle is completely withdrawn from the combination barrel 3) Flip the metal combination resetting clip, located at the exposed end of the combination barrel, through 180 degrees 4) Reset the dials wheels to a combination of your choice (we recommend that you record your new combination code and store it in a safe place) 5) Flip the metal combination resetting clip through 180 degrees back to its original position 6) Insert the lock shackle back into the combination barrel and scramble the wheels to lock <p>Security rating:</p> <table border="1" data-bbox="492 993 878 1094"> <thead> <tr> <th>Type</th> <th>Security rating</th> </tr> </thead> <tbody> <tr> <td>K750L180</td> <td style="background-color: #FFD700;">5</td> </tr> </tbody> </table> <p>Shackle Dimensions:</p> <table border="1" data-bbox="492 1167 1112 1276"> <thead> <tr> <th>Dimensions mm</th> <th>Cable Dia (mm)</th> <th>Cable Length (mm)</th> </tr> </thead> <tbody> <tr> <td>K750L180</td> <td>12</td> <td>1800</td> </tr> </tbody> </table> <p>Recommended applications - Bicycles</p>	Type	Security rating	K750L180	5	Dimensions mm	Cable Dia (mm)	Cable Length (mm)	K750L180	12	1800
Type	Security rating										
K750L180	5										
Dimensions mm	Cable Dia (mm)	Cable Length (mm)									
K750L180	12	1800									
Standards compliance	None applicable										
User health and safety information	None applicable										
RoHS/WEEE compliance	This product range does not fall within the scope of RoHS or WEEE regulations										
Material safety data	None applicable										
Warranty	<p>KASP locks are guaranteed against defects in manufacture and/or materials for 10 years</p> <p>Damage caused through inappropriate use or attempted break in is not covered</p>										
Country of origin	China										

Dimensional details

Item	Product only				Product on primary packaging			
	Width mm	Depth mm	Height mm	Net weight g	Width mm	Depth mm	Height mm	Gross weight g
K750L180	120	70	170	566	120	70	200	580