



PIN OUT

P1	P2	Colour
1. 2. 3	1	Yellow
4. 5. 6	2	Black
7. 8. 9	4	Red
10. 11. 12	3	Black

NOTE:

1. ELECTRICAL TEST:

- <1>. 100% OPEN SHORT & MISS WIRE TEST.
- <2>. Min. INSULATION RESISTANCE: Min. DC300V 2Mohm.
- <3>. Max. CONDUCTOR RESISTANCE: 10ohm.

6	PLACKING	PE Bag	Transparent	PE	1PC		
5	TYPE OF PLUG	Big 4P F	Transparent	45P PVC	1PC		
4	PIN OF PLUG	Big 4P M Terminal		Tinned copper	4PCS		
3	CORD SPECIFICATION	1007/18AWG/1C,OD=2.0	Yellow	65P PVC	1PC	150mm	
		1007/18AWG/1C,OD=2.0	Black		2PCS	150mm	
		1007/18AWG/1C,OD=2.0	Red		1PC	150mm	
2	TYPE OF PLUG	SATA 15P F	Black	45P PVC	1PC		
1	PIN OF PLUG	SATA15P F Terminal	Black	Gold plated	1PC		
ITEM	NAME	SPECIFICATION	COLOUR	MATERIAL	QTY	SIZE	REMARK

Maxxtro®

Tolerance unless otherwise specified	Linear	0.00±	Model name: SATA 15P F to BIG 4P F cable.			
	Angles	± °	Customer No.:			
Size :A4	Unit:mm	Rev:A0	Drawing By	Approved By	Sheet	Date
Scale:1:2			AIJULUAN	-	1/1	2013-08-09