



DGC 09 M/F GENDER CHANGER

PIN OUT: 9Male 9Female

1	-----	1
2	-----	2
8	-----	8
9	-----	9
G	-----	G

Label: yellow color with black character

One side: MINI GENDER CHANGER

The other side: U.S.A. PATENT 5199906 GENERAL CHANGER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 VO

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 1000V AC for one minute

INSULATOR RESISTANCE: 1000MΩ min at 500V DC

TEMPERATURE: -55°C—+105°C

				Edition	A2				
				SCALE	2:1				
2	修改規格(螺牙5.2mm改6.2mm)		2003/06/30	UNIT	mm				
1	修改規格(R.O.C. PATENT 64341) MINI GENDER CHANGER		2001/11/30	Page	1/1				
Customer	REVISION	DESCRIPTION	DATE	TRUSTY INDUSTRIAL INC.					
				<small>INDICATES DIMENSIONS UNLESS OTHERWISE SPECIFIED TOLERANCES:</small> D.01: 0.20 D.05: 0.15 D.000: 0.05		PART NO.		DWG NO.	DATE
				DGC 09 MF4A		TD0002-03	30/Jun-2003		
				DRAWN <i>Jin Hao</i>	CHECKED	APPROVED			