

## VINYL-INSULATED DOUBLE CRIMP MALE DISCONNECTORS

**MAXIMUM ELECTRIC CURRENT:**

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

**MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.**

**INSULATION MATERIAL: VINYL**


**INSULATION COLOR:**

22-16A.W.G.: RED ■ 16-14A.W.G.: BLUE ■

12-10A.W.G.: YELLOW ■

**DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL**

**TERMINAL MATERIAL: BRASS**



WIRE RANGE A.W.G. mm <sup>2</sup>	ITEM NO.	NEMA TAB	DIMENSION inch(mm)						Q'TY BOX
			W	F	L	B	D	T	
22-16 A.W.G. 0.5-1.5 mm <sup>2</sup>	MDD1-110(5)	.020X.110 (0.5X2.8)	0.11 2.8	0.256 6.5	0.756 19.2	0.413 10.5	0.157 4.000	0.02 0.5	1000
	MDD1-110(8)	.032X.110 (0.8X2.8)	0.11 2.8	0.256 6.5	0.756 19.2	0.413 10.5	0.157 4.000	0.016 0.4	1000
	MDD1-187(5)	.020X.187 (0.5X4.75)	0.189 4.8	0.256 6.5	0.78 19.8	0.413 10.5	0.157 4.000	0.02 0.5	1000
	MDD1-187(8)	.032X.187 (0.8X4.75)	0.189 4.8	0.264 6.7	0.78 19.8	0.413 10.5	0.157 4.000	0.016 0.4	1000
	MDD1-250	.032X.250 (0.8X6.35)	0.25 6.35	0.303 7.7	0.858 21.8	0.413 10.5	0.157 4.000	0.016 0.4	1000
16-14 A.W.G. 1.5-2.5 mm <sup>2</sup>	MDD2-187(5)	.020X.187 (0.5X4.75)	0.189 4.8	0.256 6.5	0.78 19.8	0.413 10.5	0.185 4.700	0.02 0.5	1000
	MDD2-187(8)	.032X.187 (0.8X4.75)	0.189 4.8	0.264 6.7	0.78 19.8	0.413 10.5	0.185 4.700	0.016 0.4	1000
	MDD2-250	.032X.250 (0.8X6.35)	0.25 6.35	0.303 7.7	0.858 21.8	0.413 10.5	0.185 4.700	0.016 0.4	1000
12-10 A.W.G. 4-6 mm <sup>2</sup>	MDD5-250	.032X.250 (0.8X6.35)	0.25 6.35	0.303 7.7	0.945 24	0.512 13	0.244 6.200	0.016 0.4	500