


ME 030-500 Closed ends header



Pitch: 5.00mm(0.197inch)





SPECIFICATIONS

| | | | CUL | VDE |
|-------------|-----------------------|---------------------|----------------------------|---------|
| 負載電壓 | Rated Voltage | Bemessungsspannung | AC 300V | AC 400V |
| 負載電流 | Rated Current | Bemessungsstrom | 16A | 16A |
| 塑膠本體 | Housing Material | Isolierstofftyp | Polyamide66(UL94V-0) | |
| 焊針 | Solder Pin | Lötstift | □ 1.0mm, Brass, Tin plated | |
| 操作溫度 | Operating Temperature | Umgebungstemperatur | -40°C to + 105°C | |
| PC板孔徑 | PCB Hole Diameter | Lochdurchmesser | φ 1.5mm | |
| UL File No. | E167040 | | | |

TABLE

| Item No. | A(mm) | A(inch) |
|-------------|-------|---------|
| ME030-50002 | 11.6 | 0.457 |
| ME030-50003 | 16.6 | 0.654 |
| ME030-50004 | 21.6 | 0.850 |
| ME030-50005 | 26.6 | 1.047 |
| ME030-50006 | 31.6 | 1.244 |
| ME030-50007 | 36.6 | 1.441 |
| ME030-50008 | 41.6 | 1.638 |
| ME030-50009 | 46.6 | 1.835 |
| ME030-50010 | 51.6 | 2.031 |
| ME030-50011 | 56.6 | 2.228 |
| ME030-50012 | 61.6 | 2.425 |
| ME030-50013 | 66.6 | 2.622 |
| ME030-50014 | 71.6 | 2.819 |
| ME030-50015 | 76.6 | 3.016 |
| ME030-50016 | 81.6 | 3.213 |
| ME030-50017 | 86.6 | 3.409 |
| ME030-50018 | 91.6 | 3.606 |
| ME030-50019 | 96.6 | 3.803 |
| ME030-50020 | 101.6 | 4.000 |
| ME030-50021 | 106.6 | 4.197 |
| ME030-50022 | 111.6 | 4.394 |
| ME030-50023 | 116.6 | 4.591 |
| ME030-50024 | 121.6 | 4.787 |



PCB Layout

