

MNX ABS 150/125 LT



Sample photo

Order symbol: ABS 150/125 LT
Product nbr: 6082917
Description: Enclosure, ABS
Remarks: Smoked transparent cover

EAN: 6418074052308
EI. number:
 Finland: 3435244
 Denmark: 8212023741
 Sweden: 6082917
 Norway:

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

| Dimensions: | Length | Width | Height | Rating: |
|--------------|--------|-------|--------|---|
| mm: | 180 | 130 | 125 | Ingress Protection (EN 60529): IP 66/67 |
| inch: | 7.1 | 5.1 | 4.9 | Impact Resistance (EN 62262): IK 07 |

| Materials: | | Electrical insulation: Totally insulated Halogen free (DIN/VDE 0472, Part 815): Yes Flammability Rating (UL 746 C 5): UL 94 HB Glow Wire Test (IEC 695-2-1) °C: 650 NEMA Class: NEMA 1, 4, 4X, 6 |
|-------------------------------|-------------|--|
| Material: | ABS | |
| Base colour: | RAL 7035 | |
| Cover colour: | Smoked grey | |
| Cover screws material: | Polyamide | |
| Cover screws colour: | Black | |

| Temperatures: | | Certificates: |
|--------------------|----------------|-----------------------|
| Short term: | -40 ... 80 °C | Fimko |
| Continuous: | -40 ... 60 °C | Europe EN 62208: 2003 |
| Short term: | -40 ... 175 °F | Gost R |
| Continuous: | -40 ... 140 °F | |

| Accessories: | |
|--------------|-----------------------------------|
| MIV 150 | Mounting plate (Galvanized steel) |
| MIN 10 | DIN-15 Mounting rail |
| MIN 15 | DIN-15 Mounting rail |
| MIV 10 | DIN-35 Mounting rail |
| MIV 15 | DIN-35 Mounting rail |
| FP A 150/180 | Front plate (Aluminium) |
| HFP 180 | Front plate hinge series |
| FP 22046 | Wall fastening lug (4 pcs) |

