



Sample photo

Order symbol: PCM 100/75 T
Product nbr: 6016902
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074024503
El. number:
 Finland: 3422261
 Denmark: 8212026997
 Sweden: 2535404
 Norway: 2535502

Including: Base with metric knock-outs and TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:		Length	Width	Height	Rating:
mm:		130	80	75	Ingress Protection (EN 60529): IP 66/67
inch:		5.1	3.1	3.0	Impact Resistance (EN 62262): IK 08
Materials:					
Material:		Polycarbonate			
Base colour:		RAL 7035			
Cover colour:		Smoked grey			
Cover screws material:		Polyamide			
Cover screws colour:		Black			
Gasket material:		TPE			
Temperatures:					
Short term:		-40 ... 120 °C			
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
MIV 100		Mounting plate (Galvanized steel)			
MIN 5		DIN-15 Mounting rail			
MIN 10		DIN-15 Mounting rail			
MIV 5		DIN-35 Mounting rail			
MIV 10		DIN-35 Mounting rail			
FP A 100/130		Front plate (Aluminium)			
HFP 130		Front plate hinge series			
FP 22046		Wall fastening lug (4 pcs)			

Rating:
 Ingress Protection (EN 60529): IP 66/67
 Impact Resistance (EN 62262): IK 08
 Electrical insulation: Totally insulated
 Halogen free (DIN/VDE 0472, Part 815): Yes
 UV resistance: UL 508
 Flammability Rating (UL 746 C 5): UL 746C 5V
 Glow Wire Test (IEC 695-2-1) °C: 960
 NEMA Class: NEMA 1, 4, 4X, 6

Certificates:
 Germanischer Lloyd (GL)
 Underwriters Laboratories
 Det Norske Veritas
 Fimko
 Europe EN 62208: 2003
 UL Canada
 Gost R

