

MNX PCM 95/75 G



Sample photo

Order symbol: PCM 95/75 G
Product nbr: 6016332
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074054784
EI. number:
 Finland: 3421394
 Denmark: 8212027585
 Sweden: 2535301
 Norway:

Including: Base with metric knock-outs and PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:		Length	Width	Height	Rating:	
mm:		100	100	75	Ingress Protection (EN 60529): IP 66/67	
inch:		3.9	3.9	3.0	Impact Resistance (EN 62262): IK 08	
Materials:						
Material:		Polycarbonate			Electrical insulation: Totally insulated	
Base colour:		RAL 7035			Halogen free (DIN/VDE 0472, Part 815): Yes	
Cover colour:		RAL 7035			UV resistance: UL 508	
Cover screws material:		Polyamide			Flammability Rating (UL 746 C 5): UL 746C 5V	
Cover screws colour:		Grey			Glow Wire Test (IEC 695-2-1) °C: 960	
Gasket material:		Polyurethane			NEMA Class: NEMA 1, 4, 4X, 6, 12, 13	
Temperatures:						
Short term:		-40 ... 120 °C			Certificates: Germanischer Lloyd (GL) Underwriters Laboratories Det Norske Veritas Fimko Europe EN 62208: 2003 UL Canada Gost R	
Continuous:		-40 ... 80 °C				
Short term:		-40 ... 250 °F				
Continuous:		-40 ... 175 °F				
Accessories:						
MIV 95		Mounting plate (Galvanized steel)				
MIN 8		DIN-15 Mounting rail				
B-3		DIN-35 Mounting rail				
FP 22046		Wall fastening lug (4 pcs)				

