


9780

Max. 18 VA

AC/AC ADAPTER

- 230 VAC input voltage
- Available with EU or UK terminals
- Compliance with relevant worldwide safety standards
- Exchangeable output plugs, providing:
 - reduced stocking requirements
 - short delivery lead times
 - snap-locks for added safety



| Technical specifications | 12 V | 12 V |
|---------------------------------|---|-------------|
| <i>Input voltage:</i> | 230 VAC, 50 Hz | |
| <i>Output voltage:</i> | 12VAC | 12VAC |
| <i>Max.output power:</i> | 12VA | 18VA |
| <i>Load current:</i> | 1A | 1,5A |
| <i>Temperature range:</i> | -10°C to +40°C | |
| <i>Protection:</i> | Protected against internal short circuit by thermal fuse in primary | |
| <i>Insulation class</i> | II | |
| <i>Electrical safety</i> | EN 60950 | |
| <i>EMC, Emission</i> | EN 61000-6-3 | |
| <i>EMC, Immunity</i> | EN 61000-6-1 | |
| <i>Mains connections:</i> | EU or UK | |
| <i>Output terminals:</i> | Secondary cable w/snap-on plugs | |
| <i>Dimensions (EU mod):</i> | 63x51x42mm | 74x58x47mm |
| <i>Dimensions (UK mod):</i> | 83x57x49mm | |
| <i>Weight: UK</i> | 440g | 470g |
| <i>Weight: EU</i> | 320g | 460g |

19062006

www.mascot.no
sales@mascot.no

Main Office
PO Box 177
N-1601 FREDRIKSTAD
NORWAY
Phone: +47 69 36 43 00
Fax: +47 69 36 43 01

Mascot UK
Box 2090, Salisbury
Wiltshire SP2 2BH
UK
+44 1722 504 853
+44 845 299 1210

Mascot DE-AT-CH-BENELUX
Hirschbergstr. 28/7
D-74838 LIMBACH
GERMANY
+49 6287 95140
+49 6287 95141

Tettnanger Str. 52
D-88239 WANGEN
GERMANY
+49 7528 951677
+49 7528 951678

Mascot France
38 rue Leo Lagrange
94270 Le Kremlin Bicêtre
FRANCE
+33 1 46 58 71 85
+33 1 46 58 71 85