



Product specification

| | | | | | | |
|----------|--------------------------|------------------|------------|--------------|-----------|-----|
| Product | CAT5E UTP SOLID 24AWG×4P | | NO. | 102286 | Page | 1/2 |
| Edition | | Established Date | 2008-09-12 | Revised Date | 2010 11 4 | |
| Approval | QINBBO | Checked | | Finish | Lii | |

Configuration & Physical Characters:

| | | | |
|------------------|---|---|--|
| 1. Conductor | Material | Bare Copper | |
| | Size | 4×2×0.5mm .24AWG | |
| | Construction | 1/0.50± 0.012 | |
| 2. Insulation | Material | HD-PE | |
| | Thickness | MIN at any point: 0.15mm MAX AVG:0.20 mm | |
| | Diameter | 0.90 ± 0.01 | |
| | Colors | Blue/White-Blue | |
| | | Orange/White-Orange | |
| | | Green/White-Green | |
| | | Brown/White-Brown | |
| Elongation | MIN 300% | | |
| Tensile strength | MIN 1.682Kg/mm ² | | |
| 3. Jacket | Material | PVC | |
| | Thickness | MIN at any point: 0.43mm MAX AVG: 0.48mm | |
| | Diameter | 4.9 ± 0.2 | |
| | Colors | Grey | |
| | Package length | 220m/box | |
| | | | |
| 4. Marking | Maxxtro NETWORK Cable UTP CAT.5E 24AWG ISO/IEC 11801 xxxxxxM | | |

Maxxtro®



Product specification

| | | | | | | |
|----------|--------------------------|------------------|------------|--------------|-----------|-----|
| Product | CAT5E UTP SOLID 24AWG×4P | | NO. | 102286 | Page | 2/2 |
| Edition | | Established Date | 2008-09-12 | Revised Date | 2010 11 4 | |
| Approval | QZNGBO | Checked | | Finish | Lili | |

Electric Characters:

90m FLUKE P-LINK TEST