



LTR.	REV.	DESCRIPTION	DATE
	A	FIRST ISSUE	2010.11.6




MARKING: Maxxtro AWM STYLE 2725 60° C 30V
1P/28AWG AND 2C/24AWG USB 2.0



Pin Assignment

A MALE B MALE



ITEM No.	LENGTH	PVC COLOR	PACKING
102303	4500 ± 100MM	GRAY 687#	BLISTER
102292	4500 ± 100MM	GRAY 687#	ZB-L



Maxxtro®

USB AM/BM-XXX

④	MOLDING	OUTER MOLD: 45P PVC	9	G
③	USB-BM	USB BMALE CONNECTOR FLASH GOLD ;NICKEL PLATED SHELL	1	SET
②	USB-AM	USB AMALE CONNECTOR FLASH GOLD ;NICKEL PLATED SHELL	1	SET
①	CABLE	USB CABLE 28AWG/1P+24AWG/2C+AL+BRAID (48*0.12mm AL-MG) +PVC JACKET OD: 4.5 ± 0.2mm	L	M
NO	P/N	DESCRIPTION	QTY	UNIT

REMARK/NO	CHA.NO	SIGNATURE	DATE	SIGN	REV.	SCALE
DRAWN BY	Jason					
CHECKED BY					A	
AUDITED BY		APPROVED BY				
CRAFT		DATE	2010.11.6	PAGE	OF	