

# PRODUCT DATASHEET

## ST8A-HF 14 W/865 K 1200 mm

SubstiTUBE Advanced HF | High performance LED tubes for electronic high frequency control gears



### AREAS OF APPLICATION

- General illumination within ambient temperatures from -20...+50 °C
- Supermarkets and department stores
- Industry
- Offices, public buildings

### PRODUCT BENEFITS

- Quick, simple and safe replacement without rewiring
- Also suitable for operation at low temperatures
- No bending thanks to glass technology

### PRODUCT FEATURES

- T8 LED tube made of glass with G13 base
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime: up to 50,000 h



## TECHNICAL DATA

### Electrical data

Rated wattage	14.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal wattage	14.00 W
Nominal current	0.26 A
Type of current	AC
Power factor $\lambda$	> 0.90

### Photometrical data

Rated color temperature	6500 K
Nominal luminous flux	2100 lm
Rated luminous flux	2100 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Luminous flux	2100 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 4$ sdcn

### Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 2.00 s
Rated beam angle (half peak value)	160.00 °

### Dimensions & weight



Length with base excl. base pins/connection	1198.00 mm
Tube diameter	25.5 mm

<b>Base diameter</b>	27.5 mm
<b>Product weight</b>	208.00 g
<b>Overall length</b>	1213 mm

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+50 °C
----------------------------------	--------------

#### Lifespan

<b>Lifespan</b>	50000 h
<b>Nominal lamp life time</b>	50000 h
<b>Rated lamp life time</b>	50000 h
<b>Number of switching cycles</b>	200000

#### Additional product data

<b>Base (standard designation)</b>	G13
<b>Mercury-free</b>	Yes

#### Capabilities

<b>Dimmable</b>	No
-----------------	----

#### Certificates & standards

<b>Type of protection</b>	IP20
<b>Standards</b>	CE
<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	17 kWh/1000h

#### Country-specific categorizations

<b>Order reference</b>	ST8A-1.2M 14W/8
------------------------	-----------------

#### Logistical data

<b>Temperature range at storage</b>	-20...80 °C
-------------------------------------	-------------

#### SAFETY ADVICE

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.  
Not suitable for operation with low-loss and conventional control gears

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

---

4058075819030	Sleeves 1	1220 mm x 31 mm x 31 mm	231.00 g	1.17 dm <sup>3</sup>
4058075819047	Shipping carton box 10	1272 mm x 210 mm x 115 mm	3045.00 g	30.72 dm <sup>3</sup>

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### REFERENCES / LINKS

For current information see

▶ [www.ledvance.com/substitute](http://www.ledvance.com/substitute)

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.