

PANASONIC'S **N°1** LONGEST LASTING ALKALINE BATTERY ⁽¹⁾



LR03EVE



LR6EVE



LR14EVE



LR20EVE



6LR61EVE

(1) Average PI index of IEC 8 modes



- Panasonic's N°1 longest lasting alkaline battery ⁽¹⁾
- Exceptional performance in low, mid and high drain products

Suitable for:



Product benefits:



- High Premium alkaline range: developed to meet the power needs of today's electronic appliances
- Eco ideas: **higher energy efficiency** = less batteries needed = less impact for the environment



Anti-leak ⁽²⁾



Specifications:

Model N°	CSU EAN	Re-order N°	Batteries/ Blister	Blisters/ Carton	Cartons/ Bundle	Bundles/ Pallet
Blister						
LR03EVE	5410853044840	LR03EVE/2BP	2	12	5	164
	5410853044871	LR03EVE/4BP	4	12	5	164
LR6EVE	5410853044758	LR6EVE/2BP	2	12	5	114
	5410853044789	LR6EVE/4BP	4	12	5	114
LR14EVE	5410853045137	LR14EVE/2BP	2	12	5	75
LR20EVE	5410853045120	LR20EVE/2BP	2	12	5	40
6LR61EVE	5410853045144	6LR61EVE/1BP	1	12	5	84



Ability to remove either 2 or 4 batteries for easy storage. With perforated strip for easy opening.

Model N°	CSU EAN	Re-order N°	Batteries/ Blister	Blisters/ Carton	Cartons/ Bundle	Cartons/ Pallet
Wide Blister						
LR03EVE	5410853044796	LR03EVE/8BW 4+4F	8	12	-	360
LR6EVE	5410853044703	LR6EVE/8BW 4+4F	8	12	-	256



High impact packaging with optimal product visibility & promotional message

(1) Average PI index of IEC 8 modes

(2) No leakage if normal use

(3) keeps energy for up to 10 years when not used (LR03 - LR6 - LR14 - LR20)

Technical specifications

Evolta

Model N°	Size		Technology	Voltage (V)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
LR03EGE	S	AAA	Alkaline	1,5	44,5	10,5	11,4	10
LR6EGE	M	AA	Alkaline	1,5	50,5	14,5	23,1	10
LR14EGE	L	C	Alkaline	1,5	50,0	25,7	68,7	10
LR20EGE	XL	D	Alkaline	1,5	61,5	33,6	140,9	10
6LR61EGE	9V	9V	Alkaline	9	47,5	25,25 x 16,3	43,3	5

Pro Power

Model N°	Size		Technology	Voltage (V)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
LR03PPG	S	AAA	Alkaline	1,5	44,5	10,5	11,4	10
LR6PPG	M	AA	Alkaline	1,5	50,5	14,5	23,1	10
LR14PPG	L	C	Alkaline	1,5	50,0	25,7	68,7	10
LR20PPG	XL	D	Alkaline	1,5	61,5	33,6	140,9	10
6LR61PPG	9V	9V	Alkaline	9	47,5	25,25 x 16,3	43,3	5
3LR12PPG	-	-	Alkaline	4,5	67	62 x 22	163	5

Everyday Power

Model N°	Size		Technology	Voltage (V)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
LR03EPS	S	AAA	Alkaline	1,5	44,5	10,5	10,8	10
LR6EPS	M	AA	Alkaline	1,5	50,5	14,5	23,1	10
LR14EPS	L	C	Alkaline	1,5	50,0	25,7	66,6	10
LR20EPS	XL	D	Alkaline	1,5	61,5	33,6	136,5	10
6LR61EPS	9V	9V	Alkaline	9	47,5	25,25 x 16,3	42,9	5

Alkaline Power

Model N°	Size		Technology	Voltage (V)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
LR03APB	S	AAA	Alkaline	1,5	44,5	10,5	10,8	5
LR6APB	M	AA	Alkaline	1,5	50,5	14,5	22,8	5
LR14APB	L	C	Alkaline	1,5	50,0	25,7	66,6	5
LR20APB	XL	D	Alkaline	1,5	61,5	33,6	136,5	5
6LR61APB	9V	9V	Alkaline	9	47,5	25,25 x 16,3	42,9	5

Red Zinc

Model N°	Size		Technology	Voltage (V)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
R03RZ	S	AAA	Zinc carbon	1,5	44	10,2	8,85	3
R6RZ	M	AA	Zinc carbon	1,5	50,25	13,9	17,5	3
R14RZ	L	C	Zinc carbon	1,5	49,4	25,4	47,7	3
R20RZ	XL	D	Zinc carbon	1,5	60,7	32,9	98,5	3
6F22RZ	9V	9V	Zinc carbon	9	48,5	17,5 x 26,5	37,9	2,5
3R12RZ	-	-	Zinc carbon	4,5	67	62 x 22	110	2,5
PP9RZ	-	-	Zinc carbon	9	78	65 x 50	368,76	2

Rechargeable Evolta

Model N°	Size		Technology	Voltage (V)	Capacity (mAh) ⁽¹⁾	Height (mm)	Diameter (mm)	Weight (g)
HHR-4XXE	AAA	S	Ni-MH	1,2	900	43,9	10,2	12,6
HHR-3XXE	AA	M	Ni-MH	1,2	2450	50,35	14,2	29,2

Rechargeable Ready to Use 1900 - 750

Model N°	Size		Technology	Voltage (V)	Capacity (mAh) ⁽¹⁾	Height (mm)	Diameter (mm)	Weight (g)
HHR-4MVE	AAA	S	Ni-MH	1,2	750	44,5	10,5	13
HHR-3MVE	AA	M	Ni-MH	1,2	1900	50,5	14,5	29
HHR-2SRE	C	L	Ni-MH	1,2	2800	49,8	25,6	69,4
HHR-1SRE	D	XL	Ni-MH	1,2	2800	61,6	32,9	81,1
HHR-9SRE	9V	9V	Ni-MH	8,4	170	47,6	15,35x25,7	31,6

Rechargeable Ready to Use 1000 & telephone

Model N°	Size		Technology	Voltage (V)	Capacity (mAh) ⁽¹⁾	Height (mm)	Diameter (mm)	Weight (g)
HHR-3LVE	AA	M	Ni-MH	1,2	1000	50,5	14,5	20,35

Photo Lithium

Model N°	Technology	Voltage (V)	Capacity (mAh)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
CR2	Photo lithium	3	850	27	15,6	11,08	10
CR123	Photo lithium	3	1400	34,5	17,1	17	10
2CR5	Photo lithium	6	1400	45	17 x 34	38	10
CRP2	Photo lithium	6	1400	36	19,5 x 34	37	10
CRV3	Photo lithium	3	3300	52	14 X 28	39	10

Lithium coin

Model N°	Technology	Voltage (V)	Capacity (mAh)	Height (mm)	Diameter (mm)	Weight (g)	Shelf life
CR1025	Lithium	3	30	2,50	10,00	0,7	10
CR1216	Lithium	3	25	1,60	12,50	0,7	10
CR1220	Lithium	3	35	2,00	12,50	0,9	10
CR1616	Lithium	3	55	1,60	16,00	1,2	10
CR1620	Lithium	3	75	2,00	16,00	1,3	10
CR1632	Lithium	3	140	3,2	16,00	1,8	10
CR2012	Lithium	3	55	1,2	20,00	1,4	10
CR2016	Lithium	3	90	1,60	20,00	1,7	10
CR2025	Lithium	3	165	2,50	20,00	2,6	10
CR2032	Lithium	3	220	3,20	20,00	3,1	10
CR2354	Lithium	3	565	5,4	23,00	5,8	10
CR2430	Lithium	3	285	3,00	24,50	3,9	10
CR2450	Lithium	3	620	5,00	24,50	6,3	10

(1) Minimum capacity