

## Multi purpose cutter

VOLTAGE	18V		
MODEL	EY 45A2 LS2G		
BATTERY	EY 9L51 B(LS)		
Sawing / Cutting	Metal (EY9PM13E)	Conduit pipe outer/25.4mm, t=1.2mm	300
		Water pipe (PVC) 34mm, t=4.7mm	60
	Thin Metal (EY9PM13F)	SPC 450mm t=1.6mm	20
		Squared log 45 x 45mm	270
	Wood (EY9PW13C)	Squared log 2 x 10, 38 x 235mm	250
		Plywood 900mm t=12mm	110
Thin Wood (EY9PW13D)	Plywood 900mm t=5mm	280	

## Saws

VOLTAGE	18V		
MODEL	EY 45A1 LS1G		
BATTERY	EY 9L51 B(LS)		
Sawing	Steel pipe for ordinary piping	Outer diameter 34 (t=3.2mm)	45
		Outer diameter 48.6 (t=3.5mm)	30
		Outer diameter 89.1 (t=4.2mm)	10
	Yellow pine	2 x 4 (38 x 89mm)	80
		2 x 10 (38 x 235mm)	50

VOLTAGE	18V		14.4V	
MODEL	EY 4550 X		EY 4541 LS1S	
BATTERY	EY 9L51 B(LS)		EY 9L45 B(LS)	
Sawing	Plywood	12mm, 15mm	23m	10m
	Particle board	t=20mm x 2	13m	7m

## Angle Grinder

VOLTAGE	14.4V		
MODEL	EY 4640 LS1S		
BATTERY	EY 9L45 B(LS)		
	Reinforcing bar	Ø 10mm	35pcs

## Sealing Gun

VOLTAGE	14.4V		3.6V	
MODEL	EY 3640 LS1S*	EY 3641 LS1S*	EY 3610 LA1J**	
	Silicon	380	380	50
	Acrylic	410	410	50
	Polyuethane	190	190	30

\* Temperature 20°C Ø 5mm cutting hole, 310ml cartridge

\*\* Temperature 20°C Ø 5mm cutting hole,  
Silikon: Sikaflex-M1 320ml cartridge,  
Acryl: Konishi 330ml cartridge,  
Polyethelen: Sikaflex-221 320ml cartridge

Depending on test condition, the measurement result is sometimes different to that of operation manual.  
The table shows average values of working capacity per fully charged battery.