



## VINYL-INSULATED DOUBLE CRIMP PIGGY BACK DISCONNECTORS

**MAXIMUM ELECTRIC CURRENT:**

|        |    |    |    |    |    |    |    |
|--------|----|----|----|----|----|----|----|
| A.W.G. | 22 | 20 | 18 | 16 | 14 | 12 | 10 |
| AMP.   | 3  | 4  | 7  | 10 | 15 | 20 | 24 |

**MAXIMUM ELECTRICAL RATING:** 105°C 600 VOLTS MAX.

**INSULATION MATERIAL:** VINYL

**INSULATION COLOR:**

22-16A.W.G.: RED ■ 16-14A.W.G.: BLUE ■

12-10A.W.G.: YELLOW ■

**DOUBLE CRIMP:** WITH COPPER SLEEVE ON BARREL

**TERMINAL MATERIAL:** BRASS

| WIRE RANGE<br>A.W.G.<br>mm <sup>2</sup>       | ITEM NO.  | NEMA TAB                | DIMENSION inch(mm) |              |            |              |               |               |                |               | Q'TY BOX |
|---|-----------|-------------------------|--------------------|--------------|------------|--------------|---------------|---------------|----------------|---------------|----------|
|   |           |                         | W                  | W1           | F          | F1           | L             | B             | D              | T             |          |
| 22-16<br>A.W.G.<br>0.5-1.5<br>mm <sup>2</sup> | PBDD1-250 | .032X.250<br>(0.8X6.35) | 0.26<br>6.6        | 0.25<br>6.35 | 0.315<br>8 | 0.323<br>8.2 | 0.886<br>22.5 | 0.413<br>10.5 | 0.157<br>4.000 | 0.016<br>0.04 | 1000     |
| 16-14<br>A.W.G.<br>1.5-2.5<br>mm <sup>2</sup> | PBDD2-250 | .032X.250<br>(0.8X6.35) | 0.26<br>6.6        | 0.25<br>6.35 | 0.315<br>8 | 0.323<br>8.2 | 0.886<br>22.5 | 0.413<br>10.5 | 0.185<br>4.700 | 0.016<br>0.04 | 1000     |
| 12-10<br>A.W.G.<br>4-6<br>mm <sup>2</sup>     | PBDD5-250 | .032X.250<br>(0.8X6.35) | 0.26<br>6.6        | 0.25<br>6.35 | 0.315<br>8 | 0.323<br>8.2 | 0.945<br>24   | 0.512<br>13   | 0.244<br>6.200 | 0.016<br>0.4  | 500      |

