



Sample photo

Order symbol: PC 122008
Product nbr: 7032760
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074003676
EI. number:
 Finland: 3423438
 Electric No. Denmark: 8212002843
 Electric No. Italy: 7301045
 Electric No. Sweden: 2536125

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

| Dimensions: | | | | Rating: |
|-------------------------------------|----------------------|-------|--------|--|
| | Length | Width | Height | |
| mm: | 200 | 120 | 75 | Ingress Protection (EN 60529): IP66/IP67 |
| inch: | 7.9 | 4.7 | 3.0 | Impact Resistance (EN 62262): IK07/IK08 |
| Materials: | | | | Electrical insulation: Totally insulated |
| Material: | Polycarbonate | | | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Base colour: | RAL 7035 -light grey | | | UV resistance: UL 508 |
| Cover screws material: | Stainless steel | | | Flammability Rating: UL 746C 5V |
| Cover colour: | RAL 7035 -light grey | | | Glow Wire Test (IEC 695-2-1) °C: 960 |
| Gasket material: | Polyurethane | | | NEMA Class: NEMA 1, 4, 4X, 12, 13 |
| Temperatures: | | | | Certificates: |
| Temperature °C (short term): | -40 ... 120 °C | | | SGS Fimko |
| Temperature °C (continuous): | -40 ... 80 °C | | | Gost R |
| Temperature °F (short term): | -40 ... 250 °F | | | |
| Temperature °F (continuous): | -40 ... 175 °F | | | |

