

# Rittal – The System.

Faster – better – everywhere.

## Door-operated switch – SZ 4315.710

Date : Mar 14, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Door-operated switch – SZ 4315.710

created: 14.03.2018 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

**Design:** With connection cable

## Product features

**Dimensions:** Length: 600 mm

**Rated operating voltage:** 400 V

**Installation options:** for compact light

**For rated current (max.):** 240 V AC, 2,5 A

**Equipment (electrical):** Colour of cable: Yellow

**Rated insulation voltage:** 400 V AC

**Rated impulse withstand voltage, phase to phase:** 6000 V AC

**Packs of:** 1 pc(s).

**Weight/pack:** 0.12 kg

**EAN:** 4028177581371

**Customs tariff** 85444290

<b>number:</b>	
<b>ETIM 6.0:</b>	EC002626
<b>ETIM 5.0:</b>	EC002626
<b>eCI@ss 8.0/8.1:</b>	27189266
<b>eCI@ss 7.0/7.1:</b>	27119116
<b>eCI@ss 6.0/6.1:</b>	27119116
<b>eCI@ss 5.1/5.1.4:</b>	27189241
<b>Product description (long):</b>	SZ Door-operated switch, with connection wire for compact light, L: 600 mm, yellow
<b>Approvals</b>	
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity