


# Ring cable lug

## Ring Cable Lugs, Insulated



### SPECIFICATION:

Surface material	Tin-plated
Material	Copper

### PRODUCT RANGE:

Art. Nr.	Cross-section	Diameter	Insulation material	Colour	Voltage	Temperature range	Thickness
RND 465-00054	0.2...0.5 mm <sup>2</sup>	3.2 mm	Nylon	yellow	600 V	max. +105 °C	0.5 mm
RND 465-00020	0.2...0.5 mm <sup>2</sup>	5.3 mm	Nylon	yellow	600 V	max. +105 °C	0.5 mm
RND 465-00055	0.2...0.5 mm <sup>2</sup>	4.3 mm	Nylon	yellow	600 V	max. +105 °C	0.5 mm
RND 465-00021	0.5...1.5 mm <sup>2</sup>	3.2 mm	Vinyl	red	600 V	max. +105 °C	0.75 mm
RND 465-00022	0.5...1.5 mm <sup>2</sup>	4.3 mm	Vinyl	red	600 V	max. +105 °C	0.75 mm
RND 465-00023	0.5...1.5 mm <sup>2</sup>	5.3 mm	Vinyl	red	600 V	max. +105 °C	0.75 mm
RND 465-00024	0.5...1.5 mm <sup>2</sup>	6.4 mm	Vinyl	red	600 V	max. +105 °C	0.75 mm
RND 465-00025	0.5...1.5 mm <sup>2</sup>	8.4 mm	Vinyl	red	600 V	max. +105 °C	0.75 mm
RND 465-00026	1.5...2.5 mm <sup>2</sup>	3.2 mm	Vinyl	blue	600 V	max. +105 °C	0.8 mm
RND 465-00027	1.5...2.5 mm <sup>2</sup>	4.3 mm	Vinyl	blue	600 V	max. +105 °C	0.8 mm
RND 465-00028	1.5...2.5 mm <sup>2</sup>	5.3 mm	Vinyl	blue	600 V	max. +105 °C	0.8 mm
RND 465-00029	1.5...2.5 mm <sup>2</sup>	6.4 mm	Vinyl	blue	600 V	max. +105 °C	0.8 mm
RND 465-00030	1.5...2.5 mm <sup>2</sup>	8.4 mm	Vinyl	blue	600 V	max. +105 °C	0.8 mm
RND 465-00031	1.5...2.5 mm <sup>2</sup>	10.5 mm	Vinyl	blue	600 V	max. +105 °C	0.8 mm
RND 465-00186	4...6 mm <sup>2</sup>	4.3 mm	Vinyl	yellow	600 V	max. +105 °C	1.0 mm
RND 465-00032	4...6 mm <sup>2</sup>	5.3 mm	Vinyl	yellow	600 V	max. +105 °C	1.0 mm
RND 465-00033	4...6 mm <sup>2</sup>	6.4 mm	Vinyl	yellow	600 V	max. +105 °C	1.0 mm
RND 465-00034	4...6 mm <sup>2</sup>	8.4 mm	Vinyl	yellow	600 V	max. +105 °C	1.0 mm
RND 465-00035	4...6 mm <sup>2</sup>	10.5 mm	Vinyl	yellow	600 V	max. +105 °C	1.0 mm