


Ring cable lug

Heat-shrinkable Ring Cable Lugs, Insulated



FEATURES:

Brazed type

SPECIFICATION:

Insulation material	Polyethylene
Surface material	Tin-plated
Voltage	600 V
Material	Copper
Temperature range	+105 °C
Shrinkage temperature range	+150 °C
Shrinkage temperature max.	+150 °C
Shrinkage temperature min.	+150 °C

PRODUCT RANGE:

Art. Nr.	Cross-section	Diameter	Colour	Thickness
RND 465-00162	0.5...1.5 mm ²	3.7 mm	red	0.75 mm
RND 465-00159	0.5...1.5 mm ²	4.3 mm	red	0.75 mm
RND 465-00163	0.5...1.5 mm ²	5.3 mm	red	0.75 mm
RND 465-00164	0.5...1.5 mm ²	6.4 mm	red	0.75 mm
RND 465-00165	0.5...1.5 mm ²	8.4 mm	red	0.75 mm
RND 465-00166	0.5...1.5 mm ²	10.5 mm	red	0.75 mm
RND 465-00167	1.5...2.5 mm ²	3.7 mm	blue	0.8 mm
RND 465-00168	1.5...2.5 mm ²	4.3 mm	blue	0.8 mm
RND 465-00169	1.5...2.5 mm ²	5.3 mm	blue	0.8 mm
RND 465-00170	1.5...2.5 mm ²	6.4 mm	blue	0.8 mm
RND 465-00171	1.5...2.5 mm ²	8.4 mm	blue	0.8 mm
RND 465-00173	1.5...2.5 mm ²	10.5 mm	blue	0.8 mm
RND 465-00174	4...6 mm ²	4.3 mm	yellow	1.0 mm
RND 465-00175	4...6 mm ²	5.3 mm	yellow	1.0 mm
RND 465-00172	4...6 mm ²	6.4 mm	yellow	1.0 mm
RND 465-00176	4...6 mm ²	8.4 mm	yellow	1.0 mm
RND 465-00177	4...6 mm ²	10.5 mm	yellow	1.0 mm
RND 465-00178	4...6 mm ²	13 mm	yellow	1.0 mm